

# Veritas™ High Availability Agent for IBM Informix Dynamic Server Installation and Configuration Guide

AIX, HP-UX, Linux, Solaris

5.1

# Veritas High Availability Agent for IBM Informix Dynamic Server Installation and Configuration Guide

The software described in this book is furnished under a license agreement and may be used only in accordance with the terms of the agreement.

Agent Version: 5.1.2.0

Document version: 5.1.2.0.1

## Legal Notice

Copyright © 2011 Symantec Corporation. All rights reserved.

Symantec, the Symantec logo, Veritas, Veritas Storage Foundation, CommandCentral, NetBackup, Enterprise Vault, and LiveUpdate are trademarks or registered trademarks of Symantec corporation or its affiliates in the U.S. and other countries. Other names may be trademarks of their respective owners.

The product described in this document is distributed under licenses restricting its use, copying, distribution, and decompilation/reverse engineering. No part of this document may be reproduced in any form by any means without prior written authorization of Symantec Corporation and its licensors, if any.

THE DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID. SYMANTEC CORPORATION SHALL NOT BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH THE FURNISHING, PERFORMANCE, OR USE OF THIS DOCUMENTATION. THE INFORMATION CONTAINED IN THIS DOCUMENTATION IS SUBJECT TO CHANGE WITHOUT NOTICE.

The Licensed Software and Documentation are deemed to be commercial computer software as defined in FAR 12.212 and subject to restricted rights as defined in FAR Section 52.227-19 "Commercial Computer Software - Restricted Rights" and DFARS 227.7202, "Rights in Commercial Computer Software or Commercial Computer Software Documentation", as applicable, and any successor regulations. Any use, modification, reproduction release, performance, display or disclosure of the Licensed Software and Documentation by the U.S. Government shall be solely in accordance with the terms of this Agreement.

Symantec Corporation  
350 Ellis Street  
Mountain View, CA 94043  
<http://www.symantec.com>

# Technical Support

Symantec Technical Support maintains support centers globally. Technical Support's primary role is to respond to specific queries about product features and functionality. The Technical Support group also creates content for our online Knowledge Base. The Technical Support group works collaboratively with the other functional areas within Symantec to answer your questions in a timely fashion. For example, the Technical Support group works with Product Engineering and Symantec Security Response to provide alerting services and virus definition updates.

Symantec's support offerings include the following:

- A range of support options that give you the flexibility to select the right amount of service for any size organization
- Telephone and/or Web-based support that provides rapid response and up-to-the-minute information
- Upgrade assurance that delivers software upgrades
- Global support purchased on a regional business hours or 24 hours a day, 7 days a week basis
- Premium service offerings that include Account Management Services

For information about Symantec's support offerings, you can visit our Web site at the following URL:

[www.symantec.com/business/support/index.jsp](http://www.symantec.com/business/support/index.jsp)

All support services will be delivered in accordance with your support agreement and the then-current enterprise technical support policy.

## Contacting Technical Support

Customers with a current support agreement may access Technical Support information at the following URL:

[www.symantec.com/business/support/contact\\_techsupp\\_static.jsp](http://www.symantec.com/business/support/contact_techsupp_static.jsp)

Before contacting Technical Support, make sure you have satisfied the system requirements that are listed in your product documentation. Also, you should be at the computer on which the problem occurred, in case it is necessary to replicate the problem.

When you contact Technical Support, please have the following information available:

- Product release level

- Hardware information
- Available memory, disk space, and NIC information
- Operating system
- Version and patch level
- Network topology
- Router, gateway, and IP address information
- Problem description:
  - Error messages and log files
  - Troubleshooting that was performed before contacting Symantec
  - Recent software configuration changes and network changes

## Licensing and registration

If your Symantec product requires registration or a license key, access our technical support Web page at the following URL:

[www.symantec.com/business/support/](http://www.symantec.com/business/support/)

## Customer service

Customer service information is available at the following URL:

[www.symantec.com/business/support/](http://www.symantec.com/business/support/)

Customer Service is available to assist with non-technical questions, such as the following types of issues:

- Questions regarding product licensing or serialization
- Product registration updates, such as address or name changes
- General product information (features, language availability, local dealers)
- Latest information about product updates and upgrades
- Information about upgrade assurance and support contracts
- Information about the Symantec Buying Programs
- Advice about Symantec's technical support options
- Nontechnical presales questions
- Issues that are related to CD-ROMs or manuals

## Support agreement resources

If you want to contact Symantec regarding an existing support agreement, please contact the support agreement administration team for your region as follows:

Asia-Pacific and Japan	<a href="mailto:customercare_apac@symantec.com">customercare_apac@symantec.com</a>
Europe, Middle-East, and Africa	<a href="mailto:semea@symantec.com">semea@symantec.com</a>
North America and Latin America	<a href="mailto:supportsolutions@symantec.com">supportsolutions@symantec.com</a>

## Documentation

Product guides are available on the media in PDF format. Make sure that you are using the current version of the documentation. The document version appears on page 2 of each guide. The latest product documentation is available on the Symantec Web site.

<https://sort.symantec.com/documents>

Your feedback on product documentation is important to us. Send suggestions for improvements and reports on errors or omissions. Include the title and document version (located on the second page), and chapter and section titles of the text on which you are reporting. Send feedback to:

[doc\\_feedback@symantec.com](mailto:doc_feedback@symantec.com)

## About Symantec Connect

Symantec Connect is the peer-to-peer technical community site for Symantec's enterprise customers. Participants can connect and share information with other product users, including creating forum posts, articles, videos, downloads, blogs and suggesting ideas, as well as interact with Symantec product teams and Technical Support. Content is rated by the community, and members receive reward points for their contributions.

<http://www.symantec.com/connect/storage-management>

# Contents

Technical Support .....	4	
Chapter 1	Introducing the Veritas High Availability Agent for IBM Informix Dynamic Server .....	11
	About the Veritas agent for IBM Informix Dynamic Server .....	12
	What's new in this agent .....	12
	Supported software .....	12
	Features of the Veritas agent for IBM Informix Dynamic Server .....	13
	How the agent makes IBM Informix Dynamic Server highly available .....	14
	High availability for IBM Informix Dynamic Server instances running in Solaris zones .....	14
	How the agent makes Informix HDR highly available .....	15
	High availability for Informix HDR .....	15
	How the agent makes SDS highly available .....	15
	Informix Dynamic Server agent functions .....	16
	Online .....	16
	Offline .....	16
	Monitor .....	17
	Clean .....	17
	Action .....	18
	Preonline .....	18
	Detecting HDR Failure .....	19
	Setting up IBM Informix Dynamic Server in a VCS cluster .....	19
Chapter 2	Installing and configuring IBM Informix Dynamic Server for high availability .....	21
	About the Informix Dynamic Server .....	21
	About Shared Disk Secondary (SDS) Servers .....	22
	About Informix high availability and disaster recovery .....	24
	Basic resources to cluster an IBM Informix Dynamic Server .....	26
	Virtualizing IBM Informix Dynamic Server .....	27
	Virtualizing Informix Dynamic Server libraries .....	28

Chapter 3	Installing, upgrading, and removing the agent for IBM Informix Dynamic Server .....	31
	Before you install the Veritas agent for IBM Informix Dynamic Server .....	31
	Prerequisites for installing the agent to support Solaris zones .....	32
	About the ACC library .....	33
	Installing the ACC library .....	33
	Installing the agent in a VCS environment .....	34
	Installing the agent in VCS One environment .....	35
	Installing the agent packages using the installer .....	36
	Installing the agent package using the CLI .....	37
	Adding the agent resource type definitions to the Policy Master Server on UNIX .....	38
	Adding the agent resource type definitions to the Policy Master Server on Windows .....	40
	Removing the agent in a VCS environment .....	40
	Removing the agent in VCS One environment .....	41
	Removing the agent packages using the installer .....	42
	Removing the agent package using CLI .....	43
	Removing the agent type definition from the Policy Master system on UNIX .....	44
	Removing the agent type definition from the Policy Master system on Windows .....	44
	Removing the ACC library .....	45
	Upgrading the agent in a VCS environment .....	45
	Upgrading the agent in a VCS One environment .....	47
Chapter 4	Configuring the agent for IBM Informix Dynamic Server .....	49
	About configuring the Veritas agent for IBM Informix Dynamic Server .....	49
	Importing the agent types files in a VCS environment .....	50
	Informix Dynamic Server agent attributes .....	52
	Executing a customized monitoring program .....	55



Chapter 5	Configuring the service groups for IBM Informix Dynamic Server .....	57
	About configuring service groups for IBM Informix Dynamic Server .....	57
	Before configuring the service groups for IBM Informix Dynamic Server .....	58
	Configuring IBM Informix Dynamic Server resources for Solaris zones support .....	58
	Configuring Action script .....	58
	Configuring preonline script .....	59
	Configuring the Agent for Informix Shared Disk Configuration .....	63
Chapter 6	Troubleshooting the agent for IBM Informix Dynamic Server .....	65
	Using the correct software and operating system versions .....	65
	Meeting prerequisites .....	66
	Configuring IBM Informix Dynamic Server resources .....	66
	Verifying virtualization .....	66
	Starting the IBM Informix Dynamic Server instance outside a cluster .....	66
	Reviewing error log files .....	67
	Using IBM Informix Dynamic Server log files .....	68
	Reviewing cluster log files .....	68
	Using trace level logging .....	69
	Using trace level logging for preonline trigger .....	69
	Handling the agent failure in SDS configuration .....	70
Appendix A	Sample Configurations .....	73
	About sample configurations for the agent for IBM Informix Dynamic Server .....	73
	Sample agent type definition .....	73
	Sample agent type definition with Solaris zone support .....	74
	Sample agent type definition with Shared Disk (SD) Configuration .....	76
	Sample configuration .....	77
	Sample configuration with Solaris zone support .....	78
	Sample service group configuration .....	80
	Sample service group configuration with Solaris zone support .....	81

Appendix B      Changes introduced in previous releases ..... 83

                    Changes introduced in previous releases ..... 83

Index ..... 85

# Introducing the Veritas High Availability Agent for IBM Informix Dynamic Server

This chapter includes the following topics:

- [About the Veritas agent for IBM Informix Dynamic Server](#)
- [What's new in this agent](#)
- [Supported software](#)
- [Features of the Veritas agent for IBM Informix Dynamic Server](#)
- [How the agent makes IBM Informix Dynamic Server highly available](#)
- [How the agent makes Informix HDR highly available](#)
- [How the agent makes SDS highly available](#)
- [Informix Dynamic Server agent functions](#)
- [Detecting HDR Failure](#)
- [Setting up IBM Informix Dynamic Server in a VCS cluster](#)

# About the Veritas agent for IBM Informix Dynamic Server

The Veritas agent for Informix Dynamic Server provides high availability for all Informix Dynamic Servers in a cluster.

See the following Technical Support TechNote for the latest updates or software issues for this agent:

<http://www.symantec.com/business/support/index?page=content&id=TECH46455>

## What's new in this agent

The enhancement in this release of Informix agent is as follows:

- Added support for AIX 7.1 and Red Hat Enterprise Linux 6.0.

For information on the changes introduced in the previous releases:

See [“Changes introduced in previous releases”](#) on page 83.

## Supported software

The Veritas agent for Informix Dynamic Server supports the following software versions:

Veritas Cluster Server

- AIX—VCS 4.0, 5.0, 5.1
- HP-UX—VCS 4.1, 5.0
- Linux—VCS 4.0, 4.1, 5.0, 5.1
- Solaris—VCS 4.0, 4.1, 5.0, 5.1

and all intermediate Maintenance Packs of these major releases.

**Note:** In the software disc, no separate agent is provided for VCS 4.0 and 5.1 on Linux and Solaris. To use the agent for VCS 4.0 and 5.1 on both these platforms, use the agent provided for VCS 4.1 and 5.0 respectively.

Similarly, on AIX, to use the agent for VCS 5.1, use the agent provided for VCS 5.0

ACC Library

5.2.4.0 and later

Operating Systems	<ul style="list-style-type: none"> <li>■ AIX 5.3, 6.1, 7.1 on pSeries</li> <li>■ HP-UX 11i v2, 11i v3 on Itanium and PA-RISC</li> <li>■ Red Hat Enterprise Linux (RHEL) 4, 5 on Intel and ppc64 RHEL 6.0 on Intel</li> <li>■ SUSE Linux Enterprise Server 9, 10, 11 on Intel and ppc64</li> <li>■ Solaris 8, 9, 10 on SPARC</li> </ul>
Informix Dynamic Server	<p>7.31, 9.21, 9.30, 9.40, 10.0, 11.10, 11.50</p> <p>and all intermediate minor versions such as 7.31.UD10, 11.50.FC1, and so on.</p>

The Veritas agent for Informix Dynamic Server supports the following software versions in a VCS One environment:

Veritas Cluster Server One	VCS One 2.0, 5.0 on AIX, HP-UX, Linux, and Solaris
Operating Systems	<ul style="list-style-type: none"> <li>■ AIX 5.3, 6.1 on pSeries</li> <li>■ HP-UX 11i v2, 11i v3 on Itanium and PA-RISC</li> <li>■ Linux Red Hat Enterprise 4, 5</li> <li>■ SUSE Linux Enterprise Server 9, 10</li> <li>■ Solaris 8, 9, 10</li> </ul>
Informix Dynamic Server	<p>7.31, 9.21, 9.30, 9.40, 10.0, 11.10, 11.50</p> <p>and all intermediate minor versions of these releases.</p>

## Features of the Veritas agent for IBM Informix Dynamic Server

The following are the features of the Veritas agent for IBM Informix Dynamic Server:

- Support for validation of attributes that are based on agent functions.  
The agent can validate attributes in each agent function before the actual data processing starts.
- Support for First Failure Data Capture (FFDC)  
In case of a fault, the agent generates a huge volume of the debug logs that enable troubleshooting of the fault.
- Support for Fast First Level Monitor (FFLM)  
The agent maintains PID files based on search patterns to expedite the monitoring process.

- Support for external user-supplied monitor utilities  
The agent enables user-specified monitor utilities to be plugged in, in addition to the built-in monitoring logic. This enables administrators to completely customize the monitoring of the application.
- Delayed agent function  
The agent manages the first monitor after online for slow initializing applications.

## How the agent makes IBM Informix Dynamic Server highly available

The agent provides the following levels of application monitoring:

- Primary or Basic monitoring  
This mode has Process check and Health check monitoring options. With the default Process check option, the agent verifies that the Informix instance processes are present in the process table. Process check cannot detect whether processes are in hung or stopped states.
- Secondary or Detail monitoring  
In this mode, the agent runs a utility to verify the status of Informix instance. The agent detects application failure if the monitoring routine reports an improper function of the Informix instance processes. When this application failure occurs, the Informix instance service group fails over to another node in the cluster.  
Thus, the agent ensures high availability for Informix instance.

## High availability for IBM Informix Dynamic Server instances running in Solaris zones

Solaris provides a means of virtualizing operating system services, allowing one or more processes to run in isolation from other activity on the system. Such a "sandbox" is called a "non-global zone." Each zone can provide a rich and customized set of services. The processes that run in a "global zone" have the same set of privileges that are available on a Solaris system today.

VCS provides high availability to applications running in non-global zones by extending the failover capability to zones. VCS is installed in a global zone, and all the agents and the engine components run in the global zone. For applications running within non-global zones, agents run script entry points inside the zones. If a zone configured under VCS control faults, VCS fails over the entire service group containing the zone.

For more details refer to, *Veritas Cluster Server User's Guide*.

The Veritas agent for IBM Informix Dynamic Server is zone-aware and can monitor Informix Server instances running in non-global zones.

## How the agent makes Informix HDR highly available

When you enable the agent attribute `SecondLevelMonitor`, the agent runs the `onstat -` command to determine the state of the Informix Database Server.

Following exit codes highlight if the IDS is up and functional:

IDS Type	Exit Code	State
■ Standard database server (without HDR)	■ 5	Online
■ Primary database server	■ 5	
■ Secondary database server	■ 2	
■ Standard database server (without HDR)	225	Offline
■ Primary database server		
■ Secondary database server		
■ Standard database server (without HDR)	Any other	Unknown
■ Primary database server		
■ Secondary database server		

## High availability for Informix HDR

The Veritas agent for Informix monitors the Informix Database Server instances running as Primary and Secondary Database Servers, if the HDR is configured in manual mode (`DR_AUTO` is (0)OFF).

When an Informix Database Server fails, the cluster fails over this instance to the node configured as the failover node. It then brings up this failover node as Primary or Secondary node, based on its original configuration. During this failover the agent does not change the membership type of the Database server.

## How the agent makes SDS highly available

When the Informix Database server is configured as Shared Disk (SD), the agent uses `SDSInstances` attribute to access the next primary shared disk. Thus, the secondary shared disk now becomes the Primary shared disk. The secondary instances now identify this disk as the primary disk.

Whenever the Primary SD Server fails, a preonline trigger gets called on the new target system. This trigger finds out the first ONLINE Secondary SD and executes the action entry point which promotes it to Primary SD, using the command:

```
# onmode -d set SDS primary SDS Instance Name
```

After the secondary shared disk is successfully converted into the primary shared disk, the preonline trigger failovers the faulted node to a new target and this instance is started as Secondary shared disk. This disk automatically gets connected to the previously promoted Primary shared disk as its updater node alias. You can confirm the same using the following command.

```
# onstat -g sds verbose
```

## Informix Dynamic Server agent functions

The agent consists of resource type declarations and agent executables. The agent executables implement the online, offline, monitor and clean operations.

### Online

The online operation performs the following tasks:

- Verifies that the required attributes are set correctly.
- Verifies whether the Informix Dynamic Server instance is not already online. If the instance is online, the online operation exits immediately.
- Executes the following command in context of the user 'informix', to remove any existing IPC resources associated with the Database Server instance:

```
$ InformixDir/bin/onmode -ky
```

- Executes the following command, in context of the user 'informix', to start the Informix Dynamic Server instance:

```
$ InformixDir/bin/oninit -y 1> /dev/null 2>&1
```

- Verifies whether the Informix Dynamic Server is completely functional.
- Returns the control to HAD.

### Offline

The offline operation performs the following tasks:

- Verifies that the required attributes are set correctly.
- Verifies that the Informix Dynamic Server instance is not offline. If the instance is already offline, the operation exits immediately.



- Executes the following command, in context of the user 'informix' to stop the Informix Dynamic Server instance.  

```
$ InformixDir/bin/onmode -ky
```
- Performs the following actions, if the execution of the offline script fails:
  - Kills any existing processes that belong to this instance of Informix Dynamic Server.
  - Removes any shared memory resources associated with the existing Informix Dynamic Server instance.
- Returns the control to HAD.
- If the instance is configured as SharedDisk, then after successful completion of the Offline function the agent checks if the offline instance was SD Primary. If yes, it then promotes one of the SD Secondary to SD Primary so that other SDS nodes do not fail.

## Monitor

The monitor operation monitors the states of the Informix Dynamic Servers on all nodes within the cluster.

The operation performs the following tasks:

- Conducts a first level check to determine that the Informix Dynamic Server processes are running on the system in the cluster. If the first level check does not find these processes running on the node, the check exits immediately, and reports the instance as offline.
- Conducts a second level check if the SecondLevelMonitor attribute is set to a value greater than 0.  
During this check agent executes the following command in context of the user 'informix' to verify that the Informix Dynamic Server is completely functional.  

```
$ InformixDir/bin/onstat -
```
- Depending upon the MonitorProgram attribute, the monitor operation performs a customized check using a user-supplied monitoring utility.  
See [“Executing a customized monitoring program”](#) on page 55.

## Clean

The clean operation performs the following tasks in the event of a failure or an unsuccessful attempt to bring an Informix Dynamic Server instance online or take it offline:

- Attempts to gracefully shut down the Informix Dynamic Server instance, using the following command in context of the user 'informix'.  
`$ InformixDir/bin/onmode -ky`
- Performs the following actions, if the instance does not shut down normally:
  - Kills the remaining processes pertaining to this instance of the Informix Dynamic Server.
  - Removes any shared memory resources associated with the existing Informix Dynamic Server instance.
- Returns the control to HAD.

## Action

The Action operation enables you to perform the following predefined actions on a resource.

Action	Description
switchprim	<p>Promotes the Informix SD Secondary Server to SD Primary Server. This action expects the name of the current/failed SD Primary Informix Instance as actionargs.</p> <p>This action is executed by preonline trigger in case of SD Primary failure.</p> <p>For example,</p> <pre># hares -action infx_inst2_res switchprim -actionargs infx_inst1 -sys infx_sys1</pre>
isprimary	<p>Retrieves the Shared disk configuration of current informix instance i.e. it is configured as SD Primary or SD Secondary.</p> <p>For example,</p> <pre># hares -action infx_inst2_res isprimary -sys infx_sys1</pre>

## Preonline

The preonline operation performs the following tasks:

- Facilitates proper Informix server failover behaviour if it is configured as a SharedDisk.
- During a MANUAL switch-over, the agent checks if the current instances are SD Primary. If yes, the agent promotes one of the online SD Secondary to SD

Primary before switching the instances to a new node. The switched-over node now becomes the new SD Secondary and automatically connects to SD Primary.

- If `preonline` is called due to a `FAULT`, the agent checks if the faulted node was SD Primary. If yes, the agent promotes one of the online SD Secondary to SD Primary before switching the instances to a new node. The switched-over node now becomes the new SD Secondary and automatically connects to SD Primary.

## Detecting HDR Failure

After a database server detects an HDR failure, it writes a message to its message log (for example, `DR: receive error`) and switches off the data replication. If an HDR failure occurs, the HDR connection between the two database servers is dropped and the secondary database takes appropriate action based upon the `DR_AUTO` configuration settings.

## Setting up IBM Informix Dynamic Server in a VCS cluster

Follow the steps below to set up IBM Informix Dynamic Server in a cluster:

- Set up a VCS cluster.  
Refer to *Veritas Cluster Server Installation Guide* for more information on installing and configuring VCS.
- Install and configure IBM Informix Dynamic Server for High Availability.
- Install the Veritas High Availability agent for IBM Informix Dynamic Server.  
See [“Installing the agent in a VCS environment”](#) on page 34.  
See [“Installing the agent in VCS One environment”](#) on page 35.
- Configure the service groups for IBM Informix Dynamic Server.  
See [“About configuring service groups for IBM Informix Dynamic Server”](#) on page 57.



# Installing and configuring IBM Informix Dynamic Server for high availability

This chapter includes the following topics:

- [About the Informix Dynamic Server](#)
- [About Shared Disk Secondary \(SDS\) Servers](#)
- [About Informix high availability and disaster recovery](#)
- [Basic resources to cluster an IBM Informix Dynamic Server](#)
- [Virtualizing IBM Informix Dynamic Server](#)

## About the Informix Dynamic Server

Informix Dynamic Server is a multithreaded relational database server that exploits symmetric multiprocessor (SMP) and uniprocessor architectures. The Dynamic Server is a database server that processes requests for data from client applications. The client is an application program that you run to request information from a database.

The database server accesses the requested information from its databases and sends back the results to the client applications. Accessing the database includes activities such as coordinating concurrent requests from multiple clients, performing read and write operations to the databases, and enforcing physical and logical consistency on the data.

The Dynamic Server provides the following features:

- Client/Server architecture
- Scalability
- High performance
- Fault tolerance and high availability
- Dynamic system administration
- Distributed data queries
- Database server security

## About Shared Disk Secondary (SDS) Servers


SDS servers access the same physical disk as the primary server. Some of the key highlights of SDS servers are:

- Provide increased availability and scalability without the need to maintain multiple copies of the database.
- Since the SDS servers use fully duplexed communications with the primary servers, having multiple SDS servers have little effect on the performance of the primary server.
- SDS servers are completely compatible with both, hardware and software disk mirroring.

Since both the SD Secondary servers read from the same disk subsystem, they can equally resume the primary server role. Thus if the primary server is unavailable, either of the secondary server can resume as the primary server.

[Figure 2-1](#) illustrates a situation in which the primary server is offline.


**Figure 2-1** Primary server configured with two SD secondary server



Multiple SDS servers also provide the opportunity to offload reporting and other functionality from the primary server. For example, a system with four SDS servers can have two servers allocated for analytics and two for read-only Web site data. During the holiday season, all four SDS servers could be allocated to Web site data to support the extra traffic.

[Figure 2-2](#) illustrates a situation in which the secondary server is taking over as a primary server

**Figure 2-2** Secondary server taking over as primary server



## About Informix high availability and disaster recovery


Informix HDR provides a way to maintain a backup copy of the entire database server at more than one distinct geographical location, so that the applications can access the data quickly in the event of a catastrophic failure.

In an HDR server pair, one server works as a Primary Database Server and other as a Secondary Database Server. During normal operation, clients can connect to the primary database server and use it as they would use an ordinary database server. Clients can use the secondary database server during normal operation, but only to read the data. The secondary database server does not permit updates from client applications.

[Figure 2-3](#) represents the primary and secondary servers in a HDR pair




**Figure 2-3** Primary and Secondary servers in a HDR



If one of the database servers in an HDR pair fails, as shown in the figure below, you can redirect the clients that use that database server to the other database server in the pair. You can also change the secondary database server to a standard database server so that it can accept updates.

Figure 2-4 represents the failover of a primary HDR server

**Figure 2-4** Primary HDR server failover



The HDR Connection depends upon DR\_AUTO ONCONFIG configuration variable. If its value is 0/OFF, the secondary database server periodically attempts to re-establish communication with the primary database server.

If its value is 1 (RETAIN\_TYPE), the type of that secondary database server changes automatically to standard. If its value is 2 (REVERSE\_TYPE), the secondary database server becomes a primary database server as soon as the connection ends when the old primary server fails, rather than when the old primary server is restarted.

## Basic resources to cluster an IBM Informix Dynamic Server

A service group containing all resources that can support an IBM Informix Dynamic Server instance in a clustered environment forms a basic setup to cluster the server.

The required resources are as follows:

Disk Group	<p>A disk group contains a volume and a file system, which is a mount resource containing the IBM Informix Dynamic Server installation files.</p> <p>Use the DiskGroup resource type to create this resource. Also, create the resource on a shared disk so that you can import the group into any system in the cluster.</p>
Mount	<p>The mount resource mounts, monitors, and unmounts the file system that is dedicated to the IBM Informix Dynamic Server installation files.</p> <p>Use the Mount resource type to create this resource.</p>
Network Interface	<p>The Network Interface resource monitors the Network Interface Card (NIC) through which the IBM Informix Dynamic Server instances communicates with the other services.</p> <p>Use the NIC resource type to create this resource.</p>
Virtual IP	<p>The Virtual IP resource configures the virtual IP address dedicated to the IBM Informix Dynamic Server instance. The external services, programs and clients use this address to communicate with this instance.</p> <p>Use the IP resource type to create this resource.</p>

**Informix**

The Informix resource starts, stops, and monitors the IBM Informix Dynamic Server instance.

Use the Informix resource type to create this resource.

## Virtualizing IBM Informix Dynamic Server

To ensure that your IBM Informix Dynamic Server can function properly on any node of the cluster, you need to virtualize all the parameters that could be dependent on a particular node.

Review the following basic notes for virtualization:

**Host names**

When installing and configuring the IBM Informix Dynamic Server, ensure that you enter the virtual host name associated with the IP address used to configure the IP resource. This ensures that if the application needs to be migrated, you are not tied down by the physical IP address given to the IBM Informix Dynamic Server.

The following is an excerpt from an INFORMIXSQLHOSTS file.

```
demo_on ontlitcp infxsrvr.vxindia.veritas.com sqlexec
```

'infxsrvr.vxindia.veritas.com' refers to the hostname associated with this instance (demo\_on) of the Dynamic Server. Ensure that you use a virtual hostname for this value. The IP address associated with this hostname would then be configured within VCS using an IP resource type that can be failed over.

If the last column of this entry (sqlexec) describes a service registered via the `/etc/services` file, ensure this entry is present in the `/etc/services` file of each failover node configured for this instance. This ensures the availability of the service on the failover node.

**Path names**

Ensure that your application gets installed on a shared disk so that it is not constrained by anything that is local to the node. If this is not possible every time, make sure that the local data is available on each configured node.

If you are using raw devices on the shared disks for dbspaces, change the permissions (for the user "informix" to 660), or access mode, on the disk groups storing the Informix Dynamic Server data.

For example, if you are using VERITAS Volume Manager™, type:

```
# vxedit -g diskgroup_name \  
set group=informix user=informix mode=660 \  
volume_name
```

## Virtualizing Informix Dynamic Server libraries

For the server utilities to work, the following versions of Informix Dynamic Server (IDS) need their libraries to be linked symbolically from /usr/lib to the libraries under *InformixDir* directory.

- Informix Dynamic Server 7.31 on UNIX
- Informix Dynamic Server 9.x and later on HP-UX PA-RISC

These symbolic links are created during IDS installation, on the node on which IDS was installed. To ensure that an application successfully boots on another node after a failover, you must manually create these links on all configured failover nodes, within the Informix service group's SystemList.

### Informix Dynamic Server 7.31 on UNIX

For Informix Dynamic Server 7.31, libraries must be linked from /usr/lib to the libraries in the *InformixDir/lib* directory, on all machines within the Informix service group's SystemList. This is applicable for all Unices.

To ensure all libraries have symbolic links, perform the following steps.

## 1 Locate the libraries.

```
# ls -l InformixDir/lib
total 1947
-rw-r--r-- 1 informix informix 36496 Oct 31 13:39 cdrapi.a
drwxr-xr-x 2 informix informix 96 Oct 31 13:39 csm
-rwxr-xr-x 1 informix informix 3126 Aug 5 2006 iosm07a.so
-rwxr-xr-x 1 informix informix 10971 Aug 5 2006 ipldd07a.so
-rwxr-xr-x 1 informix informix 1980 Aug 5 2006 ismdd07b.so
-r-xr-xr-x 1 informix informix 1198415 Aug 5 2006 libbsa.so
-rwxr-xr-x 1 informix informix 739573 Oct 31 13:39 sqlrm
```

The files with .so extension are the library files that should have symbolic links from /usr/lib.

On the node where IDS was installed, the links can be located as follows:

```
# cd /usr/lib
# ls -ltac | grep informix
lrwxrwxrwx 1 root root 29 Nov 4 18:03 ismdd07b.so.20081031
-> InformixDir/lib/ismdd07b.so
lrwxrwxrwx 1 root root 29 Nov 4 18:02 ismdd07b.so
-> InformixDir/lib/ismdd07b.so
lrwxrwxrwx 1 root root 29 Nov 4 18:02 ipldd07a.so
-> InformixDir/lib/ipldd07a.so
lrwxrwxrwx 1 root root 28 Nov 4 18:02 iosm07a.so.20081031
-> InformixDir/lib/iosm07a.so
lrwxrwxrwx 1 root root 28 Nov 4 18:01 iosm07a.so
-> InformixDir/lib/iosm07a.so
```

## 2 Create the symbolic links on each configured node, if fail to exist.

```
# cd /usr/lib
# ln -s InformixDir/lib/iosm07a.so iosm07a.so
# ln -s InformixDir/lib/ipldd07a.so ipldd07a.so
# ln -s InformixDir/lib/ismdd07b.so ismdd07b.so
# ln -s InformixDir/lib/libbsa.so libbsa.so
```

Where, *InformixDir* is INFORMIXDIR, the installation directory of IDS.

## Informix Dynamic Server 9.x and later on HP-UX PA-RISC

To ensure all libraries have symbolic links, perform the following steps.

### 1 Locate the JRE library.

```
/usr/lib/informix/IDS.version-JREjavarel
```

For example, for Informix Dynamic Server version 11.50.FC1 the following link exists on the installation node.

```
# ls -ltac /usr/lib/informix/IDS.11.50.FC1-JRE1.5
lrwxr-xr-x 1 root sys 33 Nov  8 18:51 /usr/lib/informix/
IDS.11.50.FC1-JRE1.5 -> InformixDir/extend/krakatoa/jre
```

### 2 Create the symbolic link, if fail to exists.

```
# mkdir /usr/lib/informix
# cd /usr/lib/informix
# ln -s InformixDir/extend/krakatoa/jre /usr/lib/informix/
IDS.version-JREjavarel
```

Where,

*InformixDir* is INFORMIXDIR, the installation directory of the IDS.

*version* is the version of the IDS.

*javarel* is the version of the associated JRE release.

# Installing, upgrading, and removing the agent for IBM Informix Dynamic Server

This chapter includes the following topics:

- [Before you install the Veritas agent for IBM Informix Dynamic Server](#)
- [About the ACC library](#)
- [Installing the ACC library](#)
- [Installing the agent in a VCS environment](#)
- [Installing the agent in VCS One environment](#)
- [Removing the agent in a VCS environment](#)
- [Removing the agent in VCS One environment](#)
- [Removing the ACC library](#)
- [Upgrading the agent in a VCS environment](#)
- [Upgrading the agent in a VCS One environment](#)

## Before you install the Veritas agent for IBM Informix Dynamic Server

You must install the Veritas agent for IBM Informix Dynamic Server on all the systems that will host an IBM Informix Dynamic Server service group.

Ensure that you meet the following prerequisites to install the agent for IBM Informix Dynamic Server.

For VCS, do the following:

- Install and configure Veritas Cluster Server.  
For more information on installing and configuring Veritas Cluster Server, refer to the *Veritas Cluster Server Installation Guide*.
- Remove the old Informix agent, if installed.  
To remove the agent,  
See [“Removing the agent in a VCS environment”](#) on page 40.
- Install the latest version of ACC Library.  
To install or update the ACC Library package, locate the library and related documentation in the agentpack tarball:  
See [“Installing the ACC library”](#) on page 33.
- Ensure that the 'informix' login belonging to the group 'informix', with identical user and group ids exist on all systems that host the Informix Dynamic Server.
- Ensure that all the systems have sufficient shared memory to run the Informix Dynamic Server.

For VCS One, do the following:

- Install and configure Veritas Cluster Server One.  
For more information on installing and configuring Veritas Cluster Server One, refer to the *Veritas Cluster Server One Installation Guide*.
- Remove any previous version of this agent.  
To remove the agent,  
See [“Removing the agent in VCS One environment”](#) on page 41.

## Prerequisites for installing the agent to support Solaris zones

Ensure that you meet the following prerequisites to install the agent for IBM Informix Dynamic Server:

- Install Informix to support Solaris zones. For details refer to the Informix user documentation.
- Install and configure the VCS 5.0 or 5.1 environment to support Solaris zones. Refer to the VCS user documentation for details.
- Install the required version of ACC Library.



## About the ACC library

The operations of a VCS agent depend on a set of Perl modules known as the ACC library. The library must be installed on each system in the cluster that runs the agent. The ACC library contains common, reusable functions that perform tasks, such as process identification, logging, and system calls.

Instructions to install or remove the ACC library on a single system in the cluster are given in the following sections. The instructions assume that the agent's tar file has already been extracted.

## Installing the ACC library

Install the ACC library on each system in the cluster that runs an agent that depends on the ACC library.

### To install the ACC library

- 1 Log in as superuser.
- 2 Download ACC Library.

You can download either the complete Agent Pack tarball or the individual ACCLib tarball from the Symantec Operations Readiness Tools (SORT) site (<https://sort.symantec.com/agents>).

- 3 If you downloaded the complete Agent Pack tarball, navigate to the directory containing the package for the platform running in your environment.

AIX	<code>cd1/aix/vcs/application/acc_library/version_library/pkgs</code>
HP-UX	<code>cd1/hpux/generic/vcs/application/acc_library/version_library/pkgs</code>
Linux	<code>cd1/linux/generic/vcs/application/acc_library/version_library/rpms</code>
Solaris	<code>cd1/solaris/dist_arch/vcs/application/acc_library/version_library/pkgs</code>

where *dist\_arch* is *sol\_sparc* or *sol\_x64*.

- 4 If you downloaded the individual ACCLib tarball, navigate to the pkgs directory (for AIX, HP-UX, and Solaris), or rpms directory (for Linux).
- 5 Install the package. Enter **Yes** if asked to confirm overwriting of files in the existing package.

```
AIX          # installp -ac -d VRTSacclib.bff VRTSacclib

HP-UX        # swinstall -s 'pwd' VRTSacclib

Linux        # rpm -i \
              VRTSacclib-VersionNumber-GA_GENERIC.noarch.rpm

Solaris      # pkgadd -d VRTSacclib.pkg
```

## Installing the agent in a VCS environment

Install the agent for IBM Informix Dynamic Server on each node in the cluster.

### To install the agent in a VCS environment

- 1 Download the agent from the Symantec Operations Readiness Tools (SORT) site: <https://sort.symantec.com/agents>.

You can download either the complete Agent Pack tarball or an individual agent tarball.

- 2 Uncompress the file to a temporary location, say /tmp.
- 3 If you downloaded the complete Agent Pack tarball, navigate to the directory containing the package for the platform running in your environment.

```
AIX          cd1/aix/vcs/database/informix_agent/
              vcs_version/version_agent/pkgs

HP-UX        cd1/hpux/generic/vcs/database/informix_agent/
              vcs_version/version_agent/pkgs

Linux        cd1/linux/generic/vcs/database/informix_agent/
              vcs_version/version_agent/rpms

Solaris      cd1/solaris/dist_arch/vcs/database/informix_agent/
              vcs_version/version_agent/pkgs

              where, dist_arch is sol_x64 or sol_sparc
```

If you downloaded the individual agent tarball, navigate to the pkgs directory (for AIX, HP-UX, and Solaris), or rpms directory (for Linux).

4 Log in as superuser.

5 Install the package.

```
AIX      # installp -ac -d VRTSinformix.rte.bff VRTSinformix.rte
```

```
HP-UX    # swinstall -s `pwd` VRTSinformix
```

```
Linux    # rpm -ihv \  
          VRTSinformix-AgentVersion-GA_GENERIC.noarch.rpm
```

```
Solaris  # pkgadd -d . VRTSinformix
```

6 After installing the agent package, you must import the agent type configuration file. See [“Importing the agent types files in a VCS environment”](#) on page 50.

## Installing the agent in VCS One environment

You must install the agent for Informix Server on all the client systems of the VCS One cluster that will host the Informix Server service group. You can install the agent for Informix Server using the `installagpack` program or using the command line interface (CLI).

The installation of the agent packs involves the following phases:

Installing the agent packages	See <a href="#">“Installing the agent packages using the installer”</a> on page 36.
Adding the agent resource type definitions	See <a href="#">“Adding the agent resource type definitions to the Policy Master Server on UNIX”</a> on page 38. See <a href="#">“Adding the agent resource type definitions to the Policy Master Server on Windows”</a> on page 40.

---

**Note:** The `installagpack` program supports only the `-addtypes`, `-rmtypes`, `-responsefile`, and `-rsh` options. Symantec recommends that you do not use any of the other options from the `installagpack` command help output.

---

## Installing the agent packages using the installer

You can install the agent packages on one or more client systems of a specific platform type.

---

**Note:** To install the VCS One client for managing VMware ESX Servers, download the tar ball for Red Hat Enterprise Linux 4 (RHEL 4) x86 (32-bit) or RHEL 5 x86\_64

---

### Perform the following steps to install the agent packages using the installer

- 1 On the Policy Master system, download the complete Agent Pack tarball or the individual agent tarball from the Symantec Operations Readiness Tools (SORT) site: <https://sort.symantec.com/agents>.
- 2 Uncompress the file to a temporary location, say /tmp.
- 3 If you downloaded the complete Agent Pack tarball, navigate to the following directory containing the installer for the VCS One agents, for the platform running in your environment:

AIX `cdl/aix/vcsone/vcsone_version`

HP-UX `cdl/hpux/hpuxos_version/vcsone/vcsone_version`

Where *os\_version* is the HP-UX version.

Linux `cdl/linux/dist_arch/vcsone/vcsone_version`

Where *dist* is the Linux distribution and *arch* is the architecture.

Solaris `cdl/solaris/dist_arch/vcsone/vcsone_version`

Where, *dist\_arch* is 'sol\_sparc' or 'sol\_x64'.

- 4 Enter the following command to start the agent pack installation:

```
# ./installagpack [-rsh]
```

You can use the `-rsh` option if `rsh` and `rcp` are used for communication between systems instead of the default `ssh` and `scp`. This option requires that systems be preconfigured such that the `rsh` commands between systems execute without prompting for passwords or confirmations.

- 5 Enter the name of the client systems where you want to install the agents.

- 6 Choose whether to install all the agents or any specific agent. Follow the installer prompt to specify your option.
- 7 Review the output as the installation program installs the agent packages.  
You can view installation logs in the `/var/VRTS/install/logs` directory.

## Installing the agent package using the CLI

You can install the desired agent package using the CLI, on one or more client systems of a specific platform type.

### **Perform the following steps to install the agent packages using CLI**

- 1 On the Policy Master system, download the complete Agent Pack tarball or the individual agent tarball from the Symantec Operations Readiness Tools (SORT) site: <https://sort.symantec.com/agents>.
- 2 Uncompress the file to a temporary location, say `/tmp`.

- 3 If you downloaded the complete Agent Pack tarball, navigate to the following directory containing the installer for the VCS One agents, for the platform running in your environment:

AIX	# <code>cd1/aix/vcsone/vcsone_version/pkgs</code>
HP-UX	# <code>cd1/hpux/hpuxos_version/vcsone/vcsone_version/depot</code>
Linux	# <code>cd1/linux/dist_arch/vcsone/vcsone_version/rpms</code> Where, <i>dist</i> is the Linux distribution and <i>arch</i> is the architecture
Solaris	# <code>cd1/solaris/dist_arch/vcsone/vcsone_version/pkgs</code> Where <i>dist_arch</i> is 'sol_sparc' or 'sol_x64'

- 4 Type the following command on each client system to install the agent. Answer the prompt accordingly:

AIX	# <code>installp -ac -d . VRTSinformix.rte</code>
HP-UX	# <code>swinstall -s `pwd` VRTSinformix</code>
Linux	# <code>rpm -ivh VRTSinformix_rpm_filename</code>
Solaris	# <code>pkgadd -d . VRTSinformix</code>

## Adding the agent resource type definitions to the Policy Master Server on UNIX

You must add the agent resource type definitions to the Policy Master database configuration. You can perform this task from any client system in the VCS One cluster.

---

**Note:** You must add the agent resource type definitions only one time per platform type.

---

**To add the agent resource types to the policy master database configuration**

- 1 Set up RSH or SSH communications between the client system and the policy master system.

For information on configuring SSH for remote communication, refer to the *Veritas Cluster Server One Installation Guide*.

- 2 Make sure that the PM daemon is running.

```
# /opt/VRTSvcsone/bin/haclus -display
```

The output should show ClusterState is RUNNING.

- 3 Access the temporary location where you downloaded the tar ball and depending on the platform type, navigate to the directory containing the agent installer:

AIX `cdl/aix/vcsone/vcsone_version`

HP-UX `cdl/hpux/hpuxos_version/vcsone/vcsone_version`

Where *os\_version* is the HP-UX version.

Linux `cdl/linux/dist_arch/vcsone/vcsone_version`

Where *dist* is the Linux distribution and *arch* is the architecture.

Solaris `cdl/solaris/dist_arch/vcsone/vcsone_version`

Where *dist\_arch* is the sol\_sparc or sol\_x64.

- 4 Enter the command to start the agent pack installer for adding resource types to the Policy Master configuration database. Use the `-addtypes` option:

```
# ./installagpack -addtypes
```

- 5 When the installer prompts, enter the virtual IP address of the Policy Master.
- 6 Review the output as the installer verifies communication with the Policy Master system.
- 7 Choose whether to add the type definitions for all the agents or for specific agents. Follow the installer prompts to add the type definitions.
- 8 Review the output as the installer adds the agent types to the PM database configuration and copies the appropriate `types.xml` files to the PM system.

You can view installation logs in the `/var/VRTS/install/logs` directory.

## Adding the agent resource type definitions to the Policy Master Server on Windows

After you have installed the agent package, you must add the agent resource type definitions to the Policy Master database configuration. You must perform this task from the Policy Master Server.

---

**Note:** You must add the agent resource type definitions only one time per platform type.

---

**To add the agent resource types to the Policy Master Server on Windows, perform the following steps from the Policy Master Server command prompt**

- 1 Create a temporary directory on the Policy Master Server, to add the type definitions.

```
C:\> mkdir addtypes_tmp
```

- 2 Change your working directory to the temporary directory created in step 1.

```
C:\> chdir addtypes_tmp
```

- 3 Copy the agent's type xml file in to the temporary directory.

- 4 Convert this type xml file into type cmd file.

```
C:\addtypes_tmp> haconf -xmltocmd type_xml_filename.xml
```

- 5 Rename the *type\_xml\_filename.xml.cmd* file to *type\_xml\_filename.bat*

- 6 Run the batch file.

```
C:\addtypes_tmp> type_xml_filename.bat >log.txt 2>&1
```

- 7 Review the log.txt file for any errors.

- 8 Verify whether the type has been successfully added to the Policy Master Server.

```
C:\addtypes_tmp> hatype -list -platform platform_name
```

## Removing the agent in a VCS environment

You must uninstall the agent for IBM Informix Dynamic Server from a cluster while the cluster is active.



### To uninstall the agent in a VCS environment

- 1 Log in as a superuser.
- 2 Set the cluster configuration mode to read/write by typing the following command from any node in the cluster:

```
# haconf -makerw
```

- 3 Remove all IBM Informix Dynamic Server resources from the cluster. Use the following command to verify that all resources have been removed:

```
# hares -list Type=Informix
```

- 4 Remove the agent type from the cluster configuration by typing the following command from any node in the cluster:

```
# hatype -delete Informix
```

Removing the agent's type file from the cluster removes the include statement for the agent from the main.cf file, but the agent's type file is not removed from the cluster configuration directory. You can remove the agent's type file later from the cluster configuration directory.

- 5 Save these changes. Then set the cluster configuration mode to read-only by typing the following command from any node in the cluster:

```
# haconf -dump -makero
```

- 6 Use the platform's native software management program to remove the agent for IBM Informix Dynamic Server from each node in the cluster.

Execute the following command to uninstall the agent:

AIX	# installp -u VRTSinformix.rte
HP-UX	# swremove VRTSinformix
Linux	# rpm -e VRTSinformix
Solaris	# pkgrm VRTSinformix

## Removing the agent in VCS One environment

Removing the agent package involves removing the agent files from each client system where it was installed.

You can remove the packages using the agent pack installer or the command line.

See [“Removing the agent packages using the installer”](#) on page 42.

See [“Removing the agent package using CLI”](#) on page 43.

After removing the agent packages you can remove the agent type definition from the Policy Master system.

See [“Removing the agent type definition from the Policy Master system on UNIX”](#) on page 44.

See [“Removing the agent type definition from the Policy Master system on Windows”](#) on page 44.

## Removing the agent packages using the installer

You can remove all the agent packages or the desired agent package using the `uninstallagpack` program.

---

**Note:** The `uninstallagpack` program supports only the `-responsefile` and `-rsh` options. Symantec recommends that you do not use any of the other options from the `uninstallagpack` command help output.

---

### To remove the agent packages from the client systems

- 1 Freeze the service groups that hosts the application, on the system from which you want to remove the agent package.

```
# hagrps -freeze <groupname>
```

- 2 Stop the agent on all client systems before you remove the agent package from the system.

```
# haagent -stop -notransition <AgentName> -sys <system_name>
```

- 3 Ensure that the agent operations are stopped on all the cluster systems.

```
# haagent -display <AgentName>
```

- 4 Access the temporary location where you downloaded the Agent Pack and navigate to the directory containing the package for the platform running in your environment:

AIX `cd1/aix/vcsone/vcsone_version`

HP-UX `cd1/hpux/hpuxos_version/vcsone/vcsone_version`

Where *os\_version* is the HP-UX version.

Linux `cd1/linux/dist_arch/vcsone/vcsone_version`

Where *dist* is the Linux distribution and *arch* is the architecture.

Solaris `cd1/solaris/dist_arch/vcsone/vcsone_version`

Where *dist\_arch* is the *sol\_sparc* or *sol\_x64*.

- 5 Start the `uninstallagpack` program.

```
# ./uninstallagpack [-rsh]
```

- 6 Enter the name of the client systems on which you want to uninstall the agent pack. The names must be separated by spaces.
- 7 Choose whether to remove all the agent packages or a specific agent package. Follow the installer prompt to remove the agent package.
- 8 Review the output as the program verifies the agent pack that you installed and removes the agent packages.

You can view logs in the `/var/VRTS/install/logs` directory.

## Removing the agent package using CLI

You can remove a desired agent package using the CLI.

---

**Note:** You must remove this agent package from each client system in the cluster.

---

### To remove the agent for Informix Server from a client system

- ◆ Type the following command on each client system to remove the agent. Answer prompts accordingly:

AIX                   # **installp -u VRTSinformix**

HP-UX                # **swremove VRTSinformix**

Linux                # **rpm -e VRTSinformix**

Solaris              # **pkgrm VRTSinformix**

## Removing the agent type definition from the Policy Master system on UNIX

After you remove the agent packages, you can remove the agent type definitions for agents you removed, from the Policy Master system.

### To remove the agent type definition from the Policy Master system on UNIX

- 1 Navigate to the following directory on the client system.

```
# cd /opt/VRTS/install
```

- 2 Run the following command to remove the agent type definition from the Policy Master system:

```
# ./installagpack -rmtypes
```

- 3 When the installer prompts, enter the virtual IP address of the Policy Master.
- 4 Choose whether to remove the type definitions for all the agents or for specific agents. Follow the installer prompts to remove the type definitions.

You can view logs in the /var/VRTS/install/logs directory.

## Removing the agent type definition from the Policy Master system on Windows

After you remove the agent packages, you can remove the agent type definitions for agents you removed, from the Policy Master system.

**To remove the agent type definition from the Policy Master system on Windows**

- ◆ Run the following command from the Policy Master Server command prompt.  
`C:\> hatype -delete agentname_i.e._typename -platform platformname`

## Removing the ACC library

Perform the following steps to remove the ACC library.

**To remove the ACC library**

- 1 Ensure that all agents that use ACC library are removed.
- 2 Run the following command to remove the ACC library package.

AIX	# installp -u VRTSaccclib
HP-UX	# swremove VRTSaccclib
Linux	# rpm -e VRTSaccclib
Solaris	# pkgrm VRTSaccclib

## Upgrading the agent in a VCS environment

Perform the following steps to upgrade the agent with minimal disruption, in a VCS environment.

**To upgrade the agent in a VCS environment**

- 1 Persistently freeze the service groups that host the application.

```
# hagrps -freeze GroupName -persistent
```

- 2 Stop the cluster services forcibly.

```
# hastop -all -force
```

- 3 Ensure that the agent operations are stopped on all the nodes.

```
# ps -ef | grep Informix
```

- 4
- Uninstall the agent package from all the nodes. Use the platform's native software management program to remove the agent for IBM Informix Dynamic Server from each node in the cluster.

Execute the following command to uninstall the agent:

```
AIX                # installp -u VRTSinformix.rte
HP-UX              # swremove VRTSinformix
Linux              # rpm -e VRTSinformix
Solaris            # pkgrm VRTSinformix
```

- 5
- Install the new agent on all the nodes.
- See [“Installing the agent in a VCS environment”](#) on page 34.
- 6
- Copy the new InformixTypes.cf file from the agent's conf directory, to the VCS conf directory /etc/VRTSvcs/conf/config.

VCS version	Operating system	Agent types file
VCS 4.x	■ AIX	/etc/VRTSvcs/conf/sample_Informix/ InformixTypes.cf
	■ HP-UX	
	■ Linux	
	■ Solaris	
VCS 5.x	■ AIX	/etc/VRTSagents/ha/conf/Informix/ InformixTypes.cf
	■ HP-UX	
	■ Linux	
VCS 5.0	■ Solaris SPARC and x64	/etc/VRTSagents/ha/conf/Informix/ InformixTypes50.cf
VCS 5.1	■ Solaris SPARC and x64	/etc/VRTSagents/ha/conf/Informix/ InformixTypes51.cf

**Note:** If you are using Solaris SPARC or Solaris x64, copy the InformixTypes50.cf file for VCS 5.0 (and its intermediate Maintenance Packs) and InformixTypes51.cf file for VCS 5.1

- 7 Check for the changes in the resource values required, if any, due to the new agent types file.

---

**Note:** To note the list of changed attributes, compare the new type definition file with the old type definition file.

---

- 8 Start the cluster services.

```
# hastart
```

- 9 Start the agent on all nodes, if not started.

```
# haagent -start Informix -sys SystemName
```

- 10 Unfreeze the service groups once all the resources come to an online steady state.

```
# hagr -unfreeze GroupName -persistent
```

## Upgrading the agent in a VCS One environment

Perform the following steps to upgrade the agent with minimal disruption, in a VCS One environment.

### To upgrade the agent with minimal disruption, in a VCS One environment

- 1 Freeze service groups that hosts the application.

```
# hagr -freeze -propagate GroupName
```

- 2 Stop the clients forcibly. Execute the following command from the Policy Master.

```
# hastop -client -sys SystemName -force
```

- 3 Ensure that the agent operations are stopped on all the nodes.

```
# ps -ef | grep Informix
```

- 4 Uninstall the agent package from all the nodes. Type the following command on each client system to remove the agent. Answer prompts accordingly:

```
AIX                # installp -u VRTSinformix
```

```
HP-UX              # swremove VRTSinformix
```

```
Linux              # rpm -e VRTSinformix
```

```
Solaris            # pkgrm VRTSinformix
```

- 5 Install the new agent on all the nodes in the cluster.

See [“Installing the agent in VCS One environment”](#) on page 35.

- 6 Add the agent types, using the installagpack program.

See [“Adding the agent resource type definitions to the Policy Master Server on UNIX”](#) on page 38.

- 7 Check for the changes in the resource values required, if any, due to the new agent types file.

- 8 Start the clients.

```
# hastart -client
```

- 9 Start the agent on all nodes, if not started.

```
# haagent -start Informix -sys SystemName
```

- 10 Unfreeze the service groups.

```
# hagrps -unfreeze -propagate GroupName
```



# Configuring the agent for IBM Informix Dynamic Server

This chapter includes the following topics:

- [About configuring the Veritas agent for IBM Informix Dynamic Server](#)
- [Importing the agent types files in a VCS environment](#)
- [Informix Dynamic Server agent attributes](#)
- [Executing a customized monitoring program](#)

## About configuring the Veritas agent for IBM Informix Dynamic Server

After installing the Veritas agent for IBM Informix Dynamic Server, you must import the agent type configuration file. After importing this file, you can create and configure an IBM Informix Dynamic Server resource. Before you configure a resource, review the attributes table that describes the resource type and its attributes.

To view the sample agent type definition and service groups configuration.

See [“About sample configurations for the agent for IBM Informix Dynamic Server”](#) on page 73.

# Importing the agent types files in a VCS environment

To use the agent for IBM Informix Dynamic Server, you must import the agent types file into the cluster.

To import the agent types file using the Veritas Cluster Server graphical user interface

- 1 Start the Veritas Cluster Manager and connect to the cluster on which the agent is installed.
- 2 Click **File > Import Types**.
- 3 In the Import Types dialog box, select the following file:

VCS version	OperatingSystem	Agent types file
VCS 4.x	■ AIX	/etc/VRTSvcs/conf/sample_Informix/
	■ HP-UX	InformixTypes.cf
	■ Linux	
	■ Solaris	
VCS 5.x	■ AIX	/etc/VRTSagents/ha/conf/Informix/
	■ HP-UX	InformixTypes.cf
	■ Linux	
VCS 5.0	■ Solaris SPARC and x64	/etc/VRTSagents/ha/conf/Informix/InformixTypes50.cf
VCS 5.1	■ Solaris SPARC and x64	/etc/VRTSagents/ha/conf/Informix/InformixTypes51.cf

- 4 Click **Import**.
- 5 Save the VCS configuration.

The IBM Informix Dynamic Server agent type is now imported to the VCS engine.

You can now create IBM Informix Dynamic Server resources. For additional information about using the VCS GUI, refer to the *Veritas Cluster Server User's Guide*.

To import the agent types file using the Veritas Cluster Server command line interface (CLI), perform the following steps.

- 1
- Log on to any one of the systems in the cluster as the superuser.
- 2
- Create a temporary directory.

```
# mkdir ./temp

# cd ./temp
```

- 3
- Copy the sample file Types.cf.

VCS Version	Operating System	Agent types file
VCS 4.x	■ AIX	/etc/VRTSvcs/conf/sample_Informix/ InformixTypes.cf
	■ HP-UX	
	■ Linux	
	■ Solaris	
VCS 5.x	■ AIX	/etc/VRTSagents/ha/conf/Informix/ InformixTypes.cf
	■ HP-UX	
	■ Linux	
VCS 5.0	■ Solaris SPARC and x64	/etc/VRTSagents/ha/conf/Informix/ InformixTypes50.cf

The following example assumes VCS 5.0 is installed on AIX:

```
# cp /etc/VRTSagents/ha/conf/Informix/InformixTypes.cf .
```

4 Create a dummy main.cf file:

```
# echo 'include "InformixTypes.cf"' > main.cf
```

5 Create the Informix Server resource type as follows:

```
# hacf -verify .  
  
# haconf -makerw  
  
# sh main.cmd  
  
# haconf -dump
```

The IBM Informix Dynamic Server agent type is now imported to the VCS engine.

You can now create IBM Informix Dynamic Server resources. For additional information about using the VCS CLI, refer to the *Veritas Cluster Server User's Guide*.

# Informix Dynamic Server agent attributes

Refer to the required and optional attributes while configuring the agent for Informix.

Table 4-1 lists the required attributes for the Informix agent.

Table 4-1 Required attributes	
Required attributes	Description
ResLogLevel	<p>Specifies the logging detail performed by the agent for the resource. The valid values are as follows:</p> <ul style="list-style-type: none"><li>■ ERROR: Only logs error messages.</li><li>■ WARN: Logs above plus warning messages.</li><li>■ INFO: Logs above plus informational messages.</li><li>■ TRACE: Logs above plus trace messages. TRACE is very verbose and should only be used during initial configuration or for troubleshooting and diagnostic operations.</li></ul> <p>Default: INFO</p> <p>Example: INFO</p>

**Table 4-1** Required attributes (*continued*)

Required attributes	Description
DBServerName	<p>Specifies the unique name of this instance of the Database Server. This is identical to the environment variable INFORMIXSERVER needed to start the instance. It is also known by the DBSERVERNAME variable specified in the ONCONFIG configuration file.</p> <p>Default: ""</p> <p>Example: oasis_mumbai</p>
EnvFile	<p>Full path for the file to be sourced before executing the Database Server management programs. Symantec recommends to save the file on a shared disk with InformixDir.</p> <p>The shell environments supported are: ksh, sh, and csh.</p> <p>Default: ""</p> <p>Example: /space/infxll.50/envfile_demo_on</p>
InformixDir	<p>Absolute path name of the directory in which the Database Server is installed.</p> <p>Default: ""</p> <p>Example 1: /space/infxll.50</p> <p>Example 2: /usr/infx9.40</p>
ServerType	<p>Specifies the Informix IDS server configuration type.</p> <p>The valid values are:</p> <ul style="list-style-type: none"> <li>■ Standard If the Informix instance has standard configuration</li> <li>■ HDR (High-availability and Disaster Recovery) If the instance is configured as HD Primary or HD Secondary</li> <li>■ SharedDisk If the instance is configured as SD Primary or SD Secondary</li> </ul> <p><b>Note:</b> If the Instance is configured as both, HD Primary and SD Primary then ServerType should be SharedDisk.</p> <p>Default: Standard</p> <p>Example: HDR</p>

**Table 4-1** Required attributes (*continued*)

Required attributes	Description
SDSInstances	Specifies the list of all the connected SDSInstances  Default: ""  Example: infx_sds1, infx_sds2

[Table 4-2](#) lists the optional attributes for the Informix agent.

**Table 4-2** Optional attributes

Optional attribute	Description
MonitorProgram	<p>Absolute path name of an external, user-supplied monitor executable. If specified, the monitor function executes this file to perform an additional state check of the server. There are no restrictions for what actions the external monitor program performs to determine the state of the server.</p> <p>For information about setting this attribute: See <a href="#">“Executing a customized monitoring program”</a> on page 55.</p> <p>Default: ""</p> <p>Example 1: /space/infx11.50/bin/myMonitor.pl</p> <p>Example 2: /space/infx11.50/bin/monitor_demo.pl <i>arg1 arg2</i></p>
SecondLevelMonitor	<p>Used to enable second-level monitoring. Second-level monitoring is a deeper, more thorough state check of the Informix Database Server. The numeric value specifies how often the monitoring routines must run. 0 means never run the second-level monitoring routines, 1 means run routines every monitor interval, 2 means run routines every second monitor interval. This interpretation may be extended to other values.</p> <p><b>Note:</b> Exercise caution while setting SecondLevelMonitor to large numbers. For example, if the MonitorInterval is set to 60 seconds and the SecondLevelMonitor is set to 100, then the second level check is executed every 100 minutes, which may not be as often as intended. For maximum flexibility, no upper limit is defined for SecondLevelMonitor.</p> <p>Default: 0</p> <p>Example: 5</p>

## Executing a customized monitoring program

You can configure the monitor function to execute a custom monitor utility to perform a user-defined Informix Server state check. The utility is executed in the context of the user 'informix'. The environment is set by sourcing the file specified in the EnvFile attribute.

The monitor function executes the utility specified in the MonitorProgram attribute if the following conditions are satisfied:

- The MonitorProgram attribute value is set to a valid executable utility.
- The first-level process check indicates that the IBM Informix Dynamic Server instance is online.
- The SecondLevelMonitor attribute is set to 1 and the second-level check returns the server state as "online" or the SecondLevelMonitor attribute is set to a value greater than 1, but the second-level check is deferred for this monitoring cycle.

The monitor function interprets the program exit code as follows:

110 or 0	IBM Informix Dynamic Server instance is online
100 or 1	IBM Informix Dynamic Server instance is offline
Any other value	IBM Informix Dynamic Server instance is unknown

To ensure that the custom monitor utility is always available to the agent, Symantec recommends storing the file in the directory where the IBM Informix Dynamic Server is installed.





# Configuring the service groups for IBM Informix Dynamic Server

This chapter includes the following topics:

- [About configuring service groups for IBM Informix Dynamic Server](#)
- [Before configuring the service groups for IBM Informix Dynamic Server](#)
- [Configuring IBM Informix Dynamic Server resources for Solaris zones support](#)
- [Configuring Action script](#)
- [Configuring preonline script](#)
- [Configuring the Agent for Informix Shared Disk Configuration](#)

## About configuring service groups for IBM Informix Dynamic Server

Configuring the IBM Informix Dynamic Server service group involves creating the IBM Informix Dynamic Server service group, its resources, and defining attribute values for the configured resources. You must have administrator privileges to create and configure a service group.

You can configure the service groups using one of the following:

- The Cluster Manager (Java console)
- Veritas Operations Manager
- The command-line

## Before configuring the service groups for IBM Informix Dynamic Server

Before you configure the IBM Informix Dynamic Server service group, you must:

- Verify that VCS is installed and configured on all nodes in the cluster where you will configure the service group.  
Refer to the *Veritas Cluster Server Installation Guide* for more information.
- Verify that the Veritas agent for IBM Informix Dynamic Server is installed on all nodes in the cluster.  
See [“Installing the agent in a VCS environment”](#) on page 34.

## Configuring IBM Informix Dynamic Server resources for Solaris zones support

To enable the agent for IBM Informix Dynamic Server to support Solaris zones, ensure that you perform the following configuration steps:

- Install IBM Informix Dynamic Server on dedicated Solaris zones.
- Import the `InformixTypes50.cf` (for VCS 5.0) or `InformixTypes51.cf` (for VCS 5.1) file for Solaris zone support.
- Preferably, follow the Symantec recommendation of installing zones on a shared disk for convenient configuration, failover, and maintenance.
- Make sure that the name of the Solaris zone is the same as the virtual host name that you use to install and configure the IBM Informix Dynamic Server.
- In a VCS environment, ensure that you have set the value of `ContainerName` attribute to the name of the Solaris zone.  
By default the agent function executes in the Global zone.

## Configuring Action script

The Action script comprises the following two scripts:

- `switchprim`: This script facilitates the promotion of SD Secondary Server to SD Primary Server, in case SD Primary server fails.
- `isprimary`: This script retrieves the Shared Disk (SD) configuration of current Informix instance. It is thus configured as SD Primary or SD Secondary Server.

### To configure the VCS action scripts in the VCS 4.x and 5.0 environments

- 1 Verify if the symlinks are created between the action scripts and the monitor script. If the links do not exist, create them using the following commands:

For VCS 4.x

```
cd /opt/VRTSvcs/bin/Informix
mkdir actions
cd actions
ln -s /opt/VRTSvcs/bin/Informix/monitor switchprim
ln -s /opt/VRTSvcs/bin/Informix/monitor isprimary
```

For VCS 5.x

```
cd /opt/VRTSagents/ha/bin/Informix
mkdir actions
cd actions
ln -s /opt/VRTSagents/ha/bin/Informix/monitor switchprim
ln -s /opt/VRTSagents/ha/bin/Informix/monitor isprimary
```

- 2 Modify the informix agent type attribute “SupportedActions” and set it to “switchprim, isprimary”.

Refer to *Veritas Cluster Server Agent Developer's Guide* for more information.

## Configuring preonline script

In a clustered environment, if the Informix SDS Primary instance fails, it is required to promote one of the connected SD Secondary to SD primary and then failover the faulted SD Primary to other node as SD Secondary.

The existing VCS preonline script calls the Informix preonline script to facilitate smooth SDS server failover behavior.

The Informix preonline script performs the following tasks:

- Executes the “switchprim” action script which promotes one of the SD Secondary to SD Primary.
- Fails over the faulted SD Primary to next node in cluster and brings the SD Secondary online.
- Ensures that the online operation does not execute the VCS preonline script again.

**To configure the VCS preonline script in the VCS 4.x and 5.0 environments**

- 1** Verify if the symlink has been created between the preonline script and the monitor script. If not, create them using the following commands:

For VCS 4.x

```
cd /opt/VRTSvcs/bin/Informix
ln -s /opt/VRTSvcs/bin/Informix/monitor preonline
```

For VCS 5.x

```
cd /opt/VRTSagents/ha/bin/Informix
ln -s /opt/VRTSagents/ha/bin/Informix/monitor preonline
```

- 2** Navigate to \$VCS\_Home/bin/triggers directory.

- 3** In the preonline file, add the following lines to integrate the call to the Informix preonline trigger, in the main trigger script.

---

**Note:** If the preonline file does not exist, proceed to step 4.

---

```
eval 'exec /opt/VRTSperl/bin/perl -Sw $0 ${1+"$@"}'
    if 0;

use strict;
use vars;

my $vcs_home = $ENV{"VCS_HOME"};
if (!defined ($vcs_home)) {
    $vcs_home="/opt/VRTSvcs";
}

use ag_i18n_inc;
VCSAG_SET_ENVS();
if (!defined $ARGV[0]) {
    VCSAG_LOG_MSG ("W", "Failed to continue;
undefined system name", 15028);
    exit;
} elsif (!defined $ARGV[1]) {
    VCSAG_LOG_MSG ("W", "Failed to continue;
undefined group name", 15031);
    exit;
}

#Add the Informix Trigger Call here..
#-----
# Define variables..
#-----
my $sCmd = '/opt/VRTSagents/ha/bin/Informix/preonline';
my $sResLogLevel = 'TRACE'; # Define logging level..
my @lsCmdArgs = ( @ARGV, $sResLogLevel ); # Insert logging level..
my $sArgs = join ( ' ', @lsCmdArgs);
my $iExitCode = undef;
#-----
# Pass control to preonline, if it exists..
#-----
if ( -x $sCmd ) {
    VCSAG_LOG_MSG ("I", "Preonline Cmd [$sCmd] Args [$sArgs]", 15031);
```

```

system ( $sCmd, @lsCmdArgs );
#-----
# Exit if successful..
#-----
exit $iExitCode unless ( $iExitCode = $?>> 8 );
}
# Give control back to HAD.
if (defined $ARGV[3]) {
    system("$vcs_home/bin/hagrp -online -nopre $ARGV[1]
-sys $ARGV[0] -checkpartial $ARGV[3]");
    exit;
}
system("$vcs_home/bin/hagrp -online -nopre $ARGV[1] -sys $ARGV[0]");
exit;

```

#### 4 If the preonline script does not exists, perform the following:

- Navigate to the following directory.

VCS 4.x                      /etc/VRTSvcs/conf/sample\_Informix

VCS 5.x                      /etc/VRTSagents/ha/conf/Informix

- Copy the sample preonline script to the \$VCS\_HOME/bin/triggers directory.
- Ensure that the file is executable and accessible to the "root" user.

#### 5 For the service group, set the preonline flag to True.

The preonline script is now configured to facilitate Informix SDS behavior. To configure the logging level used in the preonline script, you can set the ResLogLevel attribute in the preonline wrapper. You can then view the logs in the VCS engine log, /var/VRTSvcs/log/engine\_A.log

---

**Note:** Once the preonline trigger is configured, you may see unexpected behavior while manually switching or performing online operations on the Informix service group. This behavior is a result of the control logic within the preonline trigger that protects the Informix SDS Primary Secondary relationship. For system maintenance, if you prefer to perform manual operations on the service groups, you can do so by disabling the preonline trigger as follows:

```
# hagrp -modify service_group PreOnline 0
```

---

# Configuring the Agent for Informix Shared Disk Configuration

To configure the agent for Shared Disk configuration:

- 1 Change the ServerType attribute and set this to “Shared Disk”.
- 2 Set the SDSInstances attribute to the list of all connected Shared Disk instances.
- 3 Configure the Action Scripts.  
See [“Configuring Action script”](#) on page 58.
- 4 Configure the preonline script.  
See [“Configuring preonline script”](#) on page 59.





# Troubleshooting the agent for IBM Informix Dynamic Server

This chapter includes the following topics:

- [Using the correct software and operating system versions](#)
- [Meeting prerequisites](#)
- [Configuring IBM Informix Dynamic Server resources](#)
- [Verifying virtualization](#)
- [Starting the IBM Informix Dynamic Server instance outside a cluster](#)
- [Reviewing error log files](#)
- [Handling the agent failure in SDS configuration](#)

## Using the correct software and operating system versions

Ensure that no issues arise due to incorrect software and operating system versions. For the correct versions of operating system and software to be installed on the resource systems:

See [“Supported software”](#) on page 12.

## Meeting prerequisites

Before installing the agent for IBM Informix Dynamic Server, double check that you meet the prerequisites.

For example, you must install the ACC library on VCS before installing the agent for IBM Informix Dynamic Server.

See [“Before you install the Veritas agent for IBM Informix Dynamic Server”](#) on page 31.

## Configuring IBM Informix Dynamic Server resources

Before using IBM Informix Dynamic Server resources, ensure that you configure the resources properly. For a list of attributes used to configure all IBM Informix Dynamic Server resources, refer to the agent attributes.

## Verifying virtualization

Verify that your application does not use anything that ties it down to a particular node of the cluster.

See [“Virtualizing IBM Informix Dynamic Server ”](#) on page 27.

## Starting the IBM Informix Dynamic Server instance outside a cluster

If you face problems while working with a resource, you must disable the resource within the cluster framework. A disabled resource is not under the control of the cluster framework, and so you can test the IBM Informix Dynamic Server instance independent of the cluster framework. Refer to the cluster documentation for information about disabling a resource.

You can then restart the IBM Informix Dynamic Server instance outside the cluster framework.

---

**Note:** Use the same parameters that the resource attributes define within the cluster framework while restarting the resource outside the cluster framework.

---

Execute the following commands to start, stop or monitor the IBM Informix Dynamic Server outside the cluster framework.

You must execute these commands as user 'informix', after sourcing the environment file specified by the EnvFile agent attribute.

To start        `$ InformixDir/bin/oninit -y`

To stop        `$ InformixDir/bin/onmode -ky`

To monitor     First verify whether the Informix 'oninit' parent process is running as the user 'informix'. This process forks off other helper 'child' processes.

For example,

```
# ps -ef | grep oninit | grep -v grep
informix 3657      1   1 16:33:36 ?    0:00 oninit -y
      root  3750   3660   0 16:33:39 ?    0:00 oninit -y
      root  3756   3660   0 16:33:42 ?    0:00 oninit -y
      root  3710   3660   0 16:33:38 ?    0:00 oninit -y
      root  3753   3660   0 16:33:41 ?    0:00 oninit -y
      root  3752   3660   0 16:33:41 ?    0:00 oninit -y
      root  3679   3660   0 16:33:37 ?    0:00 oninit -y
      root  3751   3660   0 16:33:40 ?    0:00 oninit -y
      root  3660   3657   0 16:33:36 ?    0:00 oninit -y
      root  3661   3660   0 16:33:36 ?    0:00 oninit -y
      root  3755   3660   0 16:33:42 ?    0:00 oninit -y
      root  3754   3660   0 16:33:41 ?    0:00 oninit -y
```

In the above example the process with PID 3657 is the parent 'oninit' process. The agent essentially monitors this process.

Now, execute the following command and verify the exit code.

```
$ InformixDir/bin/onstat -
$ echo $?
5
```

An exit code of 5 implies that the Database Server is online and healthy.

An exit code of 255 implies that the Database Server is offline.

For all other exit codes the agent reports the application status as unknown.

## Reviewing error log files

If you face problems while using IBM Informix Dynamic Server or the agent for IBM Informix Dynamic Server, use the log files described in this section to investigate the problems.

The common reasons for issues are as follows:

Insufficient Privileges	Files that need to be created, written to, would be created as user 'informix'. Check if necessary privileges have been set.
Incorrect port, environment or parameter settings	<p>Verify that ports have been properly configured and declared. Typically, ports from 1 through 1024 are reserved for the superuser.</p> <p>Ensure that parameters to the agent are correctly defined.</p>
Expired licenses	<p>Check the application log files for any error messages related to expired licenses.</p> <p>Ensure that the license keys/files have been placed at the appropriate location, as needed by the application.</p>
Broken symlinks, missing files, and libraries	<p>Verify your installation.</p> <p>Make sure that nothing is broken, and all dependencies for the executables are met.</p>
Insufficient disk space or system parameters	<p>Ensure that the file-system has sufficient space for creation of temporary files that the application might need.</p> <p>Verify that the kernel has been tuned for sufficient IPC resources, file descriptors and meets the hardware requirement. Consult your product documentation for these details.</p>

## Using IBM Informix Dynamic Server log files

If the Informix Dynamic Server is facing problems, you can access the server log files to further diagnose the problem.

The MSGPATH variable in the ONCONFIG file describes the location where the log file for an instance of the Database Server gets created.

For example, following is an excerpt from an ONCONFIG file

```
MSGPATH /space/infx11.50/demo2/server/online.log
```

Consult your application expert if needed.

## Reviewing cluster log files

In case of problems while using the agent for IBM Informix Dynamic Server, you can access the engine log file for more information about a particular resource. The engine log file is located at `/var/VRTSvcS/log/engine_A.log`.

## Using trace level logging

The ResLogLevel attribute controls the level of logging that is written in a cluster log file for each IBM Informix Dynamic Server resource. You can set this attribute to TRACE, which enables very detailed and verbose logging.

If you set ResLogLevel to TRACE, a very high volume of messages are produced. Symantec recommends that you localize the ResLogLevel attribute for a particular resource.

---

**Note:** Starting with version 5.1.1.0 of the ACC library, the TRACE level logs for any ACCLib based agent are generated locally at the location `/var/VRTSvcs/log/Agent_A.log`.

---

### To localize ResLogLevel attribute for a resource

- 1 Identify the resource for which you want to enable detailed logging.
- 2 Localize the ResLogLevel attribute for the identified resource:  
  

```
# hares -local Resource_Name ResLogLevel
```
- 3 Set the ResLogLevel attribute to TRACE for the identified resource:  
  

```
# hares -modify Resource_Name ResLogLevel TRACE -sys SysA
```
- 4 Test the identified resource. The function reproduces the problem that you are attempting to diagnose.
- 5 Set the ResLogLevel attribute back to INFO for the identified resource:  
  

```
# hares -modify Resource_Name ResLogLevel INFO -sys SysA
```
- 6 Review the contents of the log file. Use the time noted in Step 4 and Step 6 to diagnose the problem.

You can also contact Symantec support for more help.

## Using trace level logging for preonline trigger

While executing the preonline trigger, you can set the ResLogLevel attribute to TRACE, to enable detailed logging.

See [“Configuring preonline script”](#) on page 59.

### To set the ResLogLevel attribute for preonline trigger

- 1 Go to the \$VCS\_HOME/bin/triggers directory.
- 2 Open the preonline file, and go to this section:

```
#-----
# Define variables..
#-----
my $sCmd = '/opt/VRTSagents/ha/bin/Informix/preonline';
my $sResLogLevel = 'INFO'; # Define logging level..
my @lsCmdArgs = ( @ARGV, $sResLogLevel ); # Insert logging level..
my $sArgs = join ( ' ', @lsCmdArgs );
my $iExitCode = undef;
```

- 3 Edit the value of the ResLogLevel attribute:

```
#-----
# Define variables..
#-----
my $sCmd = '/opt/VRTSagents/ha/bin/Informix/preonline';
my $sResLogLevel = 'TRACE'; # Define logging level..
my @lsCmdArgs = ( @ARGV, $sResLogLevel ); # Insert logging level..
my $sArgs = join ( ' ', @lsCmdArgs );
my $iExitCode = undef;
```

- 4 Save and close the preonline file.

You can view the logs in the VCS engine log at /var/VRTSvcs/log/engine\_A.log and the agent log at /var/VRTSvcs/log/Informix\_A.log.

## Handling the agent failure in SDS configuration

If the agent is configured for Informix Shared Disk Configuration you may experience agent failure during the online function in the following cases:

- The SD Secondary is brought online before the SD Primary.  
 In this case the SD Secondary is unable to initialize the SDS Network with the SD Primary and thus fails to come online.

### Workaround:

- Login as a superuser
- Navigate to \$INFORMIXHOME/.VRTSInfxSDPrimDB
- Find the name of the existing SD Primary instance

- Bring the SD Primary instance online
- Bring the SD Secondary instances online
- The \$INFORMIXHOME/.VRTSInfxSDPrimDB file is corrupt.  
Login as a superuser and verify if the file is corrupt. If yes, delete the file and then bring the instance online.





# Sample Configurations

This appendix includes the following topics:

- [About sample configurations for the agent for IBM Informix Dynamic Server](#)
- [Sample agent type definition](#)
- [Sample agent type definition with Solaris zone support](#)
- [Sample agent type definition with Shared Disk \(SD\) Configuration](#)
- [Sample configuration](#)
- [Sample configuration with Solaris zone support](#)
- [Sample service group configuration](#)
- [Sample service group configuration with Solaris zone support](#)

## About sample configurations for the agent for IBM Informix Dynamic Server

The sample configuration graphically depicts the resource types, resources, and resource dependencies within the service group. Review these dependencies carefully before configuring the agent for IBM Informix Dynamic Server. For more information about these resource types, see the *Veritas Cluster Server Bundled Agents Reference Guide*.

## Sample agent type definition

This section lists the sample agent type definition files for IBM Informix Dynamic Server agent on different versions of VCS.

For VCS 4.x

```

type Informix (
    static str ArgList[] = { ResLogLevel, State, IState, EnvFile,
        InformixDir, DBServerName, ServerType, SDSInstances,
        SecondLevelMonitor, MonitorProgram }
    static keylist SupportedActions = { switchprim, isprimary }
    str ResLogLevel = INFO
    str EnvFile
    str InformixDir
    str DBServerName
    str ServerType = "Standard"
    str SDSInstances[] = {}
    int SecondLevelMonitor = 0
    str MonitorProgram
)

```

For VCS 5.0

```

type Informix (
    static boolean AEPTIMEOUT = 1
    static str AgentFile = "/opt/VRTSvcs/bin/Script50Agent"
    static str AgentDirectory = "/opt/VRTSagents/ha/bin/Informix"
    static str ArgList[] = { ResLogLevel, State, IState, EnvFile,
        InformixDir, DBServerName, ServerType, SDSInstances,
        SecondLevelMonitor, MonitorProgram }
    static keylist SupportedActions = { switchprim, isprimary }
    str ResLogLevel = INFO
    str EnvFile
    str InformixDir
    str DBServerName
    str ServerType = "Standard"
    str SDSInstances[] = {}
    int SecondLevelMonitor = 0
    str MonitorProgram
)

```

## Sample agent type definition with Solaris zone support

This section lists the sample agent type definition files with Solaris zone support, for IBM Informix Dynamic Server agent.

For VCS 5.0

```

type Informix (
    static boolean AEPTIMEOUT = 1
    static str ContainerType = Zone
    static str AgentFile = "/opt/VRTSvcs/bin/Script50Agent"
    static str AgentDirectory = "/opt/VRTSagents/ha/bin/Informix"
    static str ArgList[] = { ResLogLevel, State, IState, EnvFile,
        InformixDir, DBServerName, ServerType, SDSInstances,
        SecondLevelMonitor, MonitorProgram }
    static keylist SupportedActions = { switchprim, isprimary }
    str ResLogLevel = INFO
    str EnvFile
    str InformixDir
    str DBServerName
    str ServerType = "Standard"
    str SDSInstances[] = {}
    int SecondLevelMonitor = 0
    str MonitorProgram
    str ContainerName
)

```

### For VCS 5.1

```

type Informix (
    static int ContainerOpts{} = { RunInContainer=1, PassCInfo=0 }
    static boolean AEPTIMEOUT = 1
    static str AgentFile = "/opt/VRTSvcs/bin/Script50Agent"
    static str AgentDirectory = "/opt/VRTSagents/ha/bin/Informix"
    static str ArgList[] = { ResLogLevel, State, IState, EnvFile,
        InformixDir, DBServerName, ServerType, SDSInstances,
        SecondLevelMonitor, MonitorProgram }
    static keylist SupportedActions = { switchprim, isprimary }
    str ResLogLevel = INFO
    str EnvFile
    str InformixDir
    str DBServerName
    str ServerType = "Standard"
    str SDSInstances[] = {}
    int SecondLevelMonitor = 0
    str MonitorProgram
)

```

## Sample agent type definition with Shared Disk (SD) Configuration

This section lists the sample agent type definition with SD configuration for IBM Informix Server agent.

For VCS 4.x

```
type Informix (  
    static str ArgList[] = { ResLogLevel, State, IState, EnvFile,  
        InformixDir, DBServerName, ServerType, SDSInstances,  
        SecondLevelMonitor, MonitorProgram }  
    static keylist SupportedActions = { switchprim, isprimary }  
    str ResLogLevel = INFO  
    str EnvFile  
    str InformixDir  
    str DBServerName  
    str ServerType = "SharedDisk"  
    str SDSInstances[] = {}  
    int SecondLevelMonitor = 0  
    str MonitorProgram  
)
```

For VCS 5.0

```
type Informix (  
    static boolean AEPTIMEOUT = 1  
    static str AgentFile = "/opt/VRTSvcs/bin/Script50Agent"  
    static str AgentDirectory = "/opt/VRTSagents/ha/bin/Informix"  
    static str ArgList[] = { ResLogLevel, State, IState, EnvFile,  
        InformixDir, DBServerName, ServerType, SDSInstances,  
        SecondLevelMonitor, MonitorProgram }  
    static keylist SupportedActions = { switchprim, isprimary }  
    str ResLogLevel = INFO  
    str EnvFile  
    str InformixDir  
    str DBServerName  
    str ServerType = "SharedDisk"  
    str SDSInstances[] = {}  
    int SecondLevelMonitor = 0  
    str MonitorProgram  
)
```

# Sample configuration

This section provides a sample configuration for IBM Informix Dynamic Server agent.

```
include "types.cf"
include "InformixTypes.cf"

cluster infx11sol (
  UserNames = { admin = bIJbIDiFJeJJhRJdIG }
  Administrators = { admin }
  CredRenewFrequency = 0
  CounterInterval = 5
)

system nodeA (
)

system nodeB (
)

group InformixDemo (
  SystemList = { nodeB = 0, nodeA = 1 }
)

DiskGroup infx11_dg (
  DiskGroup = infx11dg
)

IP infx11_ip (
  Device = bge0
  Address = "10.209.73.109"
  NetMask = "255.255.252.0"
)

Informix infx11_srvr (
  EnvFile = "/space/infx11.50/envfile_demo_on2"
  InformixDir = "/space/infx11.50"
  DBServerName = demo_on2
  SecondLevelMonitor = 1
)

Mount infx11_mnt (
```

```

MountPoint = "/space/infxl1.50"
BlockDevice = "/dev/vx/dsk/infxl1dg/infxl1vol"
FSType = vxfs
MountOpt = largefiles
FsckOpt = "-y"
SecondLevelMonitor = 1
)

NIC infxl1_nic (
    Device = bge0
)

infxl1_ip requires infxl1_nic
infxl1_mnt requires infxl1_dg
infxl1_srvr requires infxl1_ip
infxl1_srvr requires infxl1_mnt

// resource dependency tree
//
// group InformixDemo
// {
//     Informix infxl1_srvr
//     {
//         Mount infxl1_mnt
//         {
//             DiskGroup infxl1_dg
//         }
//         IP infxl1_ip
//         {
//             NIC infxl1_nic
//         }
//     }
// }

```

## Sample configuration with Solaris zone support

This section provides a sample configuration with Solaris zone support for IBM Informix Dynamic Server agent.

```

include "types.cf"
include "InformixTypes50.cf"

```

```
cluster infx115 (  
  UserNames = { admin = bIJbIDiFJeJJhRJdIG }  
  Administrators = { admin }  
  HaccliUserLevel = COMMANDROOT  
)  
  
system nodeA (  
)  
  
system nodeB (  
)  
  
group InformixZone (  
  SystemList = { nodeB = 0, nodeA = 1 }  
  Administrators = { z_infx115_zone_nodeB, z_infx115_zone_nodeA }  
)  
  
DiskGroup infx115_dg (  
  DiskGroup = infx115dg  
)  
  
Informix infx115_svr (  
  EnvFile = "/space/infx11.50/envfile_demo_on2"  
  InformixDir = "/space/infx11.50"  
  DBServerName = demo_on2  
  SecondLevelMonitor = 1  
  ContainerName = infx115  
)  
  
Mount infx115_mnt (  
  MountPoint = "/space/zones/infx115"  
  BlockDevice = "/dev/vx/dsk/infx115dg/infx115vol"  
  FSType = vxfs  
  MountOpt = largefiles  
  FsckOpt = "-y"  
  SecondLevelMonitor = 1  
)  
  
NIC infx115_nic (  
  Device = bge0  
)
```

```

Zone infx115_zone (
    ZoneName = infx115
)

infx115_mnt requires infx115_dg
infx115_srvr requires infx115_zone
infx115_zone requires infx115_mnt
infx115_zone requires infx115_nic

// resource dependency tree
//
// group InformixZone
// {
//     Informix infx115_srvr
//     {
//         Zone infx115_zone
//         {
//             Mount infx115_mnt
//             {
//                 DiskGroup infx115_dg
//             }
//             NIC infx115_nic
//         }
//     }
// }

```

## Sample service group configuration


This section includes sample service groups configurations in a VCS environment.

**Figure A-1** shows a service group with an Informix Dynamic Server instance running in a VCS environment.

The service group includes a DiskGroup resource, a NIC resource, an IP resource and Mount resource, along with an Informix Dynamic Server resource.



**Figure A-1** Sample service group for an Informix Dynamic Server instance




## Sample service group configuration with Solaris zone support

This section includes sample service groups with Solaris zone support.

[Figure A-2](#) shows a service group with an Informix Dynamic Server instance running in a local zone, if the zone binaries are present on a shared disk.

The Dynamic Server itself is installed locally within the Solaris zone.

**Figure A-2** Sample service group with an Informix Dynamic Server instance



# Changes introduced in previous releases

This appendix includes the following topics:

- [Changes introduced in previous releases](#)

## Changes introduced in previous releases

The enhancements in the previous releases of Informix agent are as follows:

- The agent now supports Informix Dynamic Server on shared disk inside Solaris zones.
- Added support for VCS 5.1 on AIX, Linux, and Solaris.
- Added support for VCS One 2.0 and 5.0
- The old Enterprise Agent for IBM Informix bundled along with VCS 3.5 has been phased out and replaced by this ACCLib based agent. Hence the following attributes are no longer applicable:
  - Server
  - Home
  - ConfigFile
  - Version
  - MonScript

---

**Note:** For more information on applicable attributes: See [“Informix Dynamic Server agent attributes”](#) on page 52.

---

- Added support for Informix Shared Disk Secondary (SDS) Configuration.

# Index

## A

- About
  - Informix high availability and disaster recovery 24
- about
  - configuring service groups 57
  - SDS Servers 22
- about ACC library 33
- about Informix Dynamic Server 21
- ACC library
  - installing 33
  - removing 45
- add
  - resource type
    - Policy Master on UNIX 38
    - Policy Master Server on Windows 40
- agent
  - features 13
  - functions 16
  - importing agent types files 50
  - installing, VCS environment 34
  - optional attributes 54
  - overview 12
  - required attributes 52
  - supported software 12
  - uninstalling, VCS environment 40
  - upgrading 45
  - what's new 12
- agent attributes 52
  - DBServerName 53
  - EnvFile 53
  - InformixDir 53
  - MonitorProgram 54
  - ResLogLevel 52
  - SDSInstances 54
  - SecondLevelMonitor 54
  - ServerType 53
- agent configuration file
  - importing 50
- agent functions
  - action 18

- agent functions *(continued)*
  - clean 17
  - monitor 17
  - offline 16
  - online 16
  - preonline 18
- agent installation
  - general requirements 31
  - requirements for Solaris zones 32
  - steps to install 34

## B

- before
  - configuring the service groups 58

## C

- clustering IBM Informix Dynamic Server 26
- configure
  - Action script 58
  - Agent for Informix Shared Disk
    - Configuration 63
    - preonline script 59
- configuring monitor function 55

## D

- Detecting
  - HDR failure 19

## E

- executing custom monitor program 55

## H

- How the agent makes Informix HDR highly available 15

## I

- IBM Informix Dynamic Server
  - clustering 26
  - configuring resources 66

- IBM Informix Dynamic Server *(continued)*
  - configuring resources for Solaris zones 58
  - starting instance outside cluster 66
  - virtualization 27
    - Host names 27
    - Path names 27
- Informix HDR
  - high availability 15
- install
  - agent package
    - using CLI 37
    - using installer 36

## L

- logs
  - reviewing cluster log files 68
  - reviewing error log files 67
  - using IBM Informix Dynamic Server logs 68
  - using trace level logging 69

## R

- remove
  - agent package
    - using CLI 43
    - using installer 42
  - resource type
    - Policy Master on UNIX 44
- removing agent, VCS environment 40

## S

- sample agent type definition 73
  - Shared Disk configuration 76
  - Solaris zone support 74
- sample configuration files 77
  - Solaris zone support 78
- sample service group configuration 80
- SDS configuration
  - agent failure 70
- service group
  - sample configurations, Solaris zone support 81
- setting
  - IBM Informix Dynamic Server in a cluster 19
- Solaris zone support
  - configuring IBM Informix Dynamic Serverresources 58
  - installation requirements 32
  - sample agent type definition 74
  - sample configuration files 78

- Solaris zone support *(continued)*
  - sample service group configurations 81
- starting the IBM Informix Dynamic Server instance
  - outside a cluster 66
- supported software 12

## T

- troubleshooting
  - meeting prerequisites 66
  - reviewing error log files 67
    - reviewing cluster log files 68
    - using IBM Informix Dynamic Server log files 68
    - using trace level logging 69
  - using correct software 65
  - verifying virtualization 66

## U

- uninstalling agent, VCS environment 40
- upgrading agent 45
  - VCS One environment 47