

Cluster Server Agent for Oracle GoldenGate Installation and Configuration Guide

AIX, Linux, Solaris

7.0

VERITAS™

Veritas InfoScale™ Availability Agents

Last updated: 2021-07-07

Legal Notice

Copyright © 2020 Veritas Technologies LLC. All rights reserved.

Veritas and the Veritas Logo are trademarks or registered trademarks of Veritas Technologies LLC or its affiliates in the U.S. and other countries. Other names may be trademarks of their respective owners.

This product may contain third-party software for which Veritas is required to provide attribution to the third party ("Third Party Programs"). Some of the Third-Party Programs are available under open source or free software licenses. The License Agreement accompanying the Software does not alter any rights or obligations you may have under those open source or free software licenses. Refer to the third-party legal notices document accompanying this Veritas product or available at:

<https://www.veritas.com/about/legal/license-agreements>

The product described in this document is distributed under licenses restricting its use, copying, distribution, and decompilation/reverse engineering. No part of this document may be reproduced in any form by any means without prior written authorization of Veritas Technologies LLC and its licensors, if any.

THE DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID. VERITAS TECHNOLOGIES LLC SHALL NOT BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH THE FURNISHING, PERFORMANCE, OR USE OF THIS DOCUMENTATION. THE INFORMATION CONTAINED IN THIS DOCUMENTATION IS SUBJECT TO CHANGE WITHOUT NOTICE.

The Licensed Software and Documentation are deemed to be commercial computer software as defined in FAR 12.212 and subject to restricted rights as defined in FAR Section 52.227-19 "Commercial Computer Software - Restricted Rights" and DFARS 227.7202, et seq. "Commercial Computer Software and Commercial Computer Software Documentation," as applicable, and any successor regulations, whether delivered by Veritas as on premises or hosted services. Any use, modification, reproduction release, performance, display or disclosure of the Licensed Software and Documentation by the U.S. Government shall be solely in accordance with the terms of this Agreement.

Veritas Technologies LLC
2625 Augustine Drive
Santa Clara, CA 95054

<http://www.veritas.com>

Technical Support

Technical Support maintains support centers globally. All support services will be delivered in accordance with your support agreement and the then-current enterprise technical support policies. For information about our support offerings and how to contact Technical Support, visit our website:

<https://www.veritas.com/support>

You can manage your Veritas account information at the following URL:

<https://my.veritas.com>

If you have questions regarding an existing support agreement, please email the support agreement administration team for your region as follows:

Worldwide (except Japan)

CustomerCare@veritas.com

Japan

CustomerCare_Japan@veritas.com

Documentation

Make sure that you have the current version of the documentation. Each document displays the date of the last update on page 2. The latest documentation is available on the Veritas website:

<https://sort.veritas.com/documents>

Documentation feedback

Your feedback is important to us. Suggest improvements or report errors or omissions to the documentation. Include the document title, document version, chapter title, and section title of the text on which you are reporting. Send feedback to:

infoscaledocs@veritas.com

You can also see documentation information or ask a question on the Veritas community site:

<http://www.veritas.com/community/>

Veritas Services and Operations Readiness Tools (SORT)

Veritas Services and Operations Readiness Tools (SORT) is a website that provides information and tools to automate and simplify certain time-consuming administrative tasks. Depending on the product, SORT helps you prepare for installations and upgrades, identify risks in your datacenters, and improve operational efficiency. To see what services and tools SORT provides for your product, see the data sheet:

https://sort.veritas.com/data/support/SORT_Data_Sheet.pdf

Contents

Chapter 1	Introducing the agent for Oracle GoldenGate	5
	About the agent for Oracle GoldenGate	5
	Supported software	6
	Typical Oracle GoldenGate setup in a Cluster Server cluster	6
	Oracle GoldenGate agent functions	7
	About the agent's online function	8
Chapter 2	Installing and removing the agent for Oracle GoldenGate	10
	Before you install the agent for Oracle GoldenGate	10
	Installing the agent for Oracle GoldenGate	11
	Installing the agent IPS package on Oracle Solaris 11 systems	12
	Removing the agent for Oracle GoldenGate	12
	Upgrading the agent for Oracle GoldenGate	13
Chapter 3	Configuring the agent for Oracle GoldenGate	14
	Resource type definition and attributes for the GoldenGate agent	14
	Sample configuration for the GoldenGate agent	16
	Sample configuration for the GoldenGate agent for Oracle PDBs	20
	Before you configure the agent for Oracle GoldenGate	24
	Configuring the VCS service group for GoldenGate	25
	Configuring the VCS service group for GoldenGate using Cluster Manager (Java console)	25
	Configuring the VCS service group for GoldenGate using the CLI	26
Chapter 4	Managing and testing clustering support for Oracle GoldenGate	27
	How VCS recovers from various disasters in an HA/DR setup with Oracle GoldenGate	27
	Testing the global service group migration	30
	Testing disaster recovery after host failure	31

Introducing the agent for Oracle GoldenGate

This chapter includes the following topics:

- [About the agent for Oracle GoldenGate](#)
- [Supported software](#)
- [Typical Oracle GoldenGate setup in a Cluster Server cluster](#)
- [Oracle GoldenGate agent functions](#)

About the agent for Oracle GoldenGate

The Cluster Server agent for Oracle GoldenGate provides failover and recovery support for Oracle databases that are protected by the Oracle GoldenGate replication feature in a VCS global cluster. The agent supports active/passive bi-directional configurations in which Oracle GoldenGate replicates data from an active primary database to a full replica database on a live standby system. The standby system is ready for failover during planned and unplanned outages.

The agent also support Oracle PDBs on Red Hat Enterprise Linux (RHEL) platforms.

Considerations to be made for GoldenGate configurations with this agent:

- The agent does not support HA for the Replicat process. If Replicat is configured on multiple systems in a cluster, GoldenGate might duplicate the records in the database.
- The agent requires the trail files that are used for GoldenGate replication to be located on the shared disk.
- The agent does not support the default configuration for Oracle 12c when GoldenGate is installed on the shared disk.

Supported software


For information on the software versions that the InfoScale (VCS) agent for GoldenGate supports, see the Veritas Services and Operations Readiness Tools (SORT) site:

<https://sort.veritas.com/agents>

Typical Oracle GoldenGate setup in a Cluster Server cluster

Figure 1-1 displays a typical cluster setup in a GoldenGate environment.

Figure 1-1 Typical clustering setup for the agent



Clustering in a GoldenGate environment typically consists of the following hardware infrastructure:

- The primary database instance (db1) sends change records data across a TCP/IP link to a live standby database instance (db2) using Oracle GoldenGate. A local cluster protects the primary database and makes it highly available.

- The live standby database instance applies the redo information to a physical copy of the primary database using Oracle GoldenGate Replicat.
- The primary and live standby sites must be connected through a single TCP/IP network connection. This link can be shared with VCS global clusters for heartbeat communication.
- Network heartbeating between the two data centers to determine their health; this network heartbeating could be TCP/IP.

Oracle GoldenGate agent functions

The Oracle GoldenGate agent monitors and manages the state of replicated Oracle Database that runs on Cluster Server nodes. Agent functions bring resources online, take them offline, and perform different monitoring actions.

online	<p>The agent starts the specified Extract and data pump, if configured.</p> <p>The agent runs the following Oracle GoldenGate command to start the Extract:</p> <pre>START EXTRACT EXTRACT</pre> <p>See “About the agent’s online function” on page 8.</p>
offline	<p>Removes the lock file that was created for the resource by the online function.</p> <p>The agent does not run any Oracle GoldenGate commands because taking the resource offline is not indicative of the intention to stop Extract.</p> <p>Note: The offline function stops the GoldenGate replication. Transactions that take place in the Oracle database after the GoldenGate resource is offline might cause data loss.</p>
monitor	<p>Verifies the status of the Extract and takes the following action:</p> <ul style="list-style-type: none">■ If the Extract status is RUNNING, the monitor function reports the status of the resource as online.■ If the Extract status is STOPPED, the monitor function reports the status of the resource as offline.■ If the Extract status is ABENDED, the monitor function reports the status of the resource as offline and reports a warning that the Extract is in the ABENDED state.
open	<p>The agent verifies the status of the Extract.</p> <p>The agent does not verify the Extract status if the agent was started after running the following command:</p> <pre>hastop<-all -local> -force</pre>
clean	<p>Determines if it is safe to fault the resource when the online function fails or times out.</p>

action/StartExtract	Starts the specified Extract and data pump, if configured, with the following command: <code>START EXTRACT <i>EXTRACT</i> .</code>
action/StopExtract	Runs internally during a planned switchover operation. This action function stops the specified Extract and data pump, if configured, with the following command: <code>STOP EXTRACT <i>EXTRACT</i> .</code>
action/StartReplicat	Runs internally during a planned switchover operation. This action function starts the specified Replicat with the following command: <code>START REPLICAT <i>REPLICAT</i> .</code>
action/StopReplicat	Stops the specified Replicat with the following command: <code>STOP REPLICAT <i>REPLICAT</i> .</code>
action/GGStatus	Displays the status of the Extract, Replicat, Oracle database, and data pump, if configured.
action /GetExtractLag	Runs internally for calculating the RPO. This action function uses the following command to get the lag of the specified Extract and data pump, if configured <code>LAG EXTRACT <i>EXTRACT</i> .</code>
action/GetCurrentRPO	Fetches the current point-in-time RPO in terms of lag of the Extract, Replicat, and data pump, if configured. Invoke this action function on the DR system. Note: The agent does not store the computed RPO; make a note of the RPO for future reference.

About the agent's online function

The agent checks whether the Oracle GoldenGate Manager process is running and if it is not, the agent attempts to start the process.

The agent also checks the status of the Extract that is configured in the GoldenGate resource and takes the following actions:

- If the state of the Extract is **RUNNING**, the agent comes online directly.
- If the state of the Extract is **STOPPED** and the state of the Replicat is neither **STOPPED** nor **ABENDED**, the agent verifies that the state of the remote cluster is **RUNNING**. The agent then attempts to switch roles in the following manner:
- If the state of the both the Extract and the Replicat is **STOPPED**, the agent checks the state of the remote Replicat. If the state of the remote Replicat is

RUNNING, the agent considers this as a scenario to perform a local failover operation; the agent starts the local Extract and data pump, if configured.

1. The agent calls the StopExtract action function on the remote cluster to stop the Extract from capturing logs on the remote database. The StopExtract function first verifies that there is no lag in the Extract and data pump, if configured, and then stops the Extract and data pump.
2. The agent verifies that there are no more records to be processed by the Replicat. The agent then stops the local Replicat.
3. The agent alters the local Extract on the local database, in order to begin capturing logs on the local database. The agent then starts the local Extract and data pump, if configured.
4. The agent calls the StartReplicat action function on the remote cluster. This starts the Replicat on the remote database, and the Replicat accepts the changes captured from the Extract.

If the remote cluster state is not RUNNING, the agent considers this as a disaster to the primary database.

If the value of the AutoTakeover attribute is 0, the agent does not take any action.

If the value of the AutoTakeover attribute is 1, the agent performs the following steps to convert the local database to primary.

1. The agent verifies that there are no more records to be processed by the local Replicat. The agent then stops the local Replicat.
2. The agent alters the local Extract on the local database, in order to begin capturing logs on the local database. The agent then starts the local Extract. The local Extract then captures all the changes on the database during a disaster. These changes are applied on the failed primary when the primary comes back online.

After the direction of replication is successfully switched, the agent marks the status of the Oracle GoldenGate resource as online.

Installing and removing the agent for Oracle GoldenGate

This chapter includes the following topics:

- [Before you install the agent for Oracle GoldenGate](#)
- [Installing the agent for Oracle GoldenGate](#)
- [Installing the agent IPS package on Oracle Solaris 11 systems](#)
- [Removing the agent for Oracle GoldenGate](#)
- [Upgrading the agent for Oracle GoldenGate](#)

Before you install the agent for Oracle GoldenGate

Before you install the agent for Oracle GoldenGate, ensure that the following prerequisites are met:

- Before you install the Cluster Server agent for Oracle GoldenGate, ensure that you install and configure the VCS on all nodes in the cluster..
- Install Oracle GoldenGate and set up Oracle GoldenGate replication between the Oracle databases and set up the required hardware infrastructure. See [“Typical Oracle GoldenGate setup in a Cluster Server cluster”](#) on page 6.
- The agent for Oracle GoldenGate requires the GoldenGate Manager process to be running on the primary and live standby databases.

Installing the agent for Oracle GoldenGate

You must install the Oracle GoldenGate agent on each node in the cluster. In global cluster environments, install the agent on each node in each cluster.

To install the agent in a VCS environment

- 1 Download the Agent Pack from the Veritas Services and Operations Readiness Tools (SORT) site: <https://sort.veritas.com/agents>.

You can download the complete Agent Pack `tar` file or the individual agent `tar` file.

- 2 Uncompress the file to a temporary location, say `/tmp`.
- 3 If you downloaded the complete Agent Pack `tar` file, navigate to the directory that contains the package for the platform that is applicable to your environment.

```
AIX      cd1/aix/vcs/replication/goldengate_agent/  
agent_version/pkgsg/
```

```
Linux    cd1/linux/generic/vcs/replication/goldengate_agent/  
agent_version/rpms/
```

```
Solaris  cd1/solaris/dist_arch/vcs/replication/goldengate_agent/  
agent_version/pkgsg/
```

(AIX, HP-UX, or Solaris) If you downloaded the individual agent `tar` file, navigate to the `pkgsg` directory.

(Linux) If you downloaded the individual agent `tar` file, navigate to the `rpms` directory.

- 4 Log in as a superuser.
- 5 Install the package.

```
AIX      # installp -ac -d VRTSvcsogg.rte.bff VRTSvcsogg.rte
```

```
Linux    # rpm -ihv \  
VRTSvcsogg-AgentVersion-Linux_GENERIC.noarch.rpm
```

```
Solaris  # pkgadd -d . VRTSvcsogg
```

Note: On successful installation of the agent, if VCS is running, the agent types definition is automatically added to the VCS configuration.

Installing the agent IPS package on Oracle Solaris 11 systems

To install the agent IPS package on an Oracle Solaris 11 system

1 Copy the `VRTSvcsogg.p5p` package from the `pkgs` directory to the system in the `/tmp/install` directory.

2 Disable the publishers that are not reachable as package install may fail, if any of the already added repositories are unreachable.

```
# pkg set-publisher --disable <publisher name>
```

where the publisher name is obtained using the `pkg publisher` command.

3 Add a file-based repository in the system.

```
# pkg set-publisher -g /tmp/install/VRTSvcsogg.p5p Veritas
```

4 Install the package.

```
# pkg install --accept VRTSvcsogg
```

5 Remove the publisher from the system.

```
# pkg unset-publisher Veritas
```

6 Enable the publishers that were disabled earlier.

```
# pkg set-publisher --enable <publisher name>
```

Removing the agent for Oracle GoldenGate

Before you attempt to remove the agent, make sure the application service group is not online.

You must remove the GoldenGate agent from each node in the cluster.

To remove the agent, type the following command on each node. Answer prompts accordingly:

```
AIX          # installp -u VRTSvcsogg.rte
```

```
Linux        # rpm -e VRTSvcsogg
```

```
Solaris      # pkgrm VRTSvcsogg
```

Note: To uninstall the agent IPS package on a Solaris 11 system:

```
# pkg uninstall VRTSvcsogg
```

Upgrading the agent for Oracle GoldenGate

You must upgrade the agent on each node in the cluster.

To upgrade the agent software

- 1 Save the VCS configuration and stop the VCS engine.

```
# haconf -dump -makero  
# hastop -all -force
```

- 2 Remove the agent from the node.

See [“Removing the agent for Oracle GoldenGate”](#) on page 12.

- 3 Delete the file `/etc/VRTSvcs/conf/config/GoldenGateTypes.cf`.

- 4 Install the current version of the agent.

See [“Installing the agent for Oracle GoldenGate”](#) on page 11.

- 5 If the agent types file was not added automatically on successful installation of the agent, add the agent types file. To add the file, copy the file `GoldenGateTypes.cf` from the directory `/etc/VRTSvcs/conf/` to the `/etc/VRTSvcs/conf/config` directory.

- 6 Repeat step 2 through step 5 on each node.

- 7 From a node in the cluster, edit your configuration file `/etc/VRTSvcs/conf/config/main.cf`.

Configure the new attributes, if applicable.

- 8 Verify the configuration

```
# hacf -verify config
```

- 9 Start VCS on local node first.

- 10 Start VCS on other nodes.

Configuring the agent for Oracle GoldenGate

This chapter includes the following topics:

- [Resource type definition and attributes for the GoldenGate agent](#)
- [Sample configuration for the GoldenGate agent](#)
- [Sample configuration for the GoldenGate agent for Oracle PDBs](#)
- [Before you configure the agent for Oracle GoldenGate](#)
- [Configuring the VCS service group for GoldenGate](#)

Resource type definition and attributes for the GoldenGate agent

The resource type definition defines the agent in VCS.

The resource type definition for the GoldenGate agent is as follows:

```
type GoldenGate (
    static keylist RegList = { ComputedRSLA }
    static keylist SupportedActions = {StartExtract, StopExtract,
        StartReplicat, StopReplicat, GetExtractLag, GetCurrentRPO}
    static int OnlineRetryLimit = 1
    static int OnlineTimeout = 1200
    static int RestartLimit = 1
    static str ArgList[] = { LinkRes, GoldenGateHome, Extract,
        DataPump, Replicat, AutoTakeover, ComputedRSLA}
    str LinkRes
    str Extract
```

```

str DataPump
str Replicat
str GoldenGateHome = "/u01/app/oracle/product/gg"
int AutoTakeover = 0
int ComputeDRSLA = 1
)

```

Review the description of the following agent attributes and assign values to the required attributes.

Table 3-1 Attributes for the Oracle GoldenGate agent


Attribute	Description
LinkRes	Name of the Oracle resource that manages the replicated database instance. Type-dimension: string-scalar Example Value: Oracle_res
Extract	Name of the Oracle GoldenGate Extract which captures changes in the database instance. Type-dimension: string-scalar Example Value: PriEXT
DataPump	Name of the Oracle GoldenGate data pump. This is an optional attribute. Configure this attribute if data pump is configured in the Oracle GoldenGate replication configuration. Type-dimension: string-scalar Example Value: PriDP
Replicat	Name of the Oracle GoldenGate Replicat which processes and applies the changes on the live standby database. Type-dimension: string-scalar Example Value: StndbyREP
GoldenGateHome	Location of the Oracle GoldenGate home directory. Type-dimension: string-scalar Default: /u01/app/oracle/product/gg

Table 3-1 Attributes for the Oracle GoldenGate agent (*continued*)

Attribute	Description
AutoTakeover	<p>Indicates if the agent must bring the resource online on the live standby database when the primary database is not available.</p> <ul style="list-style-type: none"> ■ If the value of this attribute is set to 0, the agent does not bring the resource online on the live standby database when the primary database is not available. ■ If the value of this attribute is set to 1, the agent brings the resource online on the live standby database when the primary database is not available. <p>Type-dimension: integer-scalar Default: 0</p>
ComputeDRSLA	<p>Used to enable Recovery Point Objective (RPO) computation. This attribute cannot be edited.</p> <p>Type-dimension : integer-scalar Default value : 1</p>

Sample configuration for the GoldenGate agent

Figure 3-1 Sample dependency graph



The sample dependency graphs depict the resource types, resources, and resource dependencies within the service group. Cluster Server service group has a resource

of type GoldenGate. A second service group contains all necessary resources to control the database instance. The Oracle_GG group depends on the Oracle_DB group, which is an online local hard group dependency.

Note the following variations to a standard Oracle database cluster configuration:

- The Oracle resource depends on the Listener resource. The listener process must be already active when the database instance is started.
- The IP and NIC resource in the database service group are optional. These resources are only necessary if a cluster on its own protects the primary database. For wide area or site failover, you can implement a transparent network client reconnect.
- If either the primary cluster or the remote cluster has more than one node, you must configure an IP resource for GoldenGate replication. If both the primary cluster and remote cluster have only a single node, configuring this IP resource is optional.
- The name of the GoldenGate resource must be the same in each global cluster configuration.

You can configure a resource of the GoldenGate type in the `main.cf` file.

Sample main.cf file for an Oracle GoldenGate agent configuration

```
include "types.cf"
include "OracleTypes.cf"
include "GoldenGateTypes.cf"

cluster vcspri (
  UserNames = { admin = gJKcJEjGKfKKiSKeJH }
  Administrators = { admin }
  CounterInterval = 5
)

remoteclass vcsdr (
  ClusterAddress = "10.xxx.xx.xx"
)

heartbeat Icmp (
  ClusterList = { vcsdr }
  AYARetryLimit = 0
  Arguments @vcsdr = { "10.xxx.xx.xx" }
)
```

```

system orarep01 (
)

group ClusterService (
  SystemList = { orarep01 = 0 }
  AutoStartList = { orarep01 }
  OnlineRetryLimit = 3
  OnlineRetryInterval = 120
)

Application wac (
  StartProgram = "/opt/VRTSvcs/bin/wacstart"
  StopProgram = "/opt/VRTSvcs/bin/wacstop"
  MonitorProcesses = { "/opt/VRTSvcs/bin/wac" }
)

NIC csgnic (
  Device = eth0
)

wac requires csgnic

// resource dependency tree
//
// group ClusterService
// {
//   Application wac
//   {
//     NIC csgnic
//   }
// }

group db_OFFDG (
  SystemList = { orarep01 = 0 }
)

DiskGroup oradg (
  DiskGroup = oradg
)

Netlsnr LSNR_OFFDG (
  Owner = oracle
  Home = "/opt/oracle/app/oracle/product/11.2.0/Db_1"
)

```

```

MonScript = "./bin/Netlsnr/LsnrTest.pl"
)

Mount oradb1 (
MountPoint = "/oradb1"
BlockDevice = "/dev/vx/dsk/oradg/oravol"
FSType = vxfs
FsckOpt = "-y"
)

Oracle OFFDG (
Critical = 0
Sid = OFFDG
Owner = oracle
Home = "/opt/oracle/app/oracle/product/11.2.0/Db_1"
StartUpOpt = CUSTOM
MonScript = "./bin/Oracle/SqlTest.pl"
)

Volume oravol (
DiskGroup = oradg
Volume = oravol
)

OFFDG requires oradb1
OFFDG requires LSNR_OFFDG
oradb1 requires oravol
oravol requires oradg

// resource dependency tree
//
// group db_OFFDG
// {
// Oracle OFFDG
//   {
//     Netlsnr LSNR_OFFDG
//     Mount oradb1
//       {
//         Volume oravol
//           {
//             DiskGroup oradg
//           }
//       }
//   }
// }

```

```

//      }
// }

group sw_OFFDG (
  SystemList = { orarep01 = 0 }
  ClusterList = { vcspri = 1, vcsdr = 0 }
  Authority = 1
  ClusterFailOverPolicy = Auto
)

GoldenGate O_goldengate (
  LinkRes = OFFDG
  GoldenGateHome = "/u01/app/oracle/product/GoldenGate"
  Extract = ext1
  DataPump = dpump1
  Replicat = repl
  AutoTakeover = 0
)

  requires group db_OFFDG online local hard


// resource dependency tree
//
// group sw_OFFDG
// {
// GoldenGate O_goldengate
// }

```

Sample configuration for the GoldenGate agent for Oracle PDBs

The sample dependency graph depicts an Oracle GoldenGate agent configuration that supports Oracle PDB. The agent requires that all the GoldenGate resources are in same service group and that separate Extract and Replicat values are configured for each PDB on both, the primary and the secondary clusters. The Oracle_GG group has an online-local-hard dependency on the Oracle_DB group.

Figure 3-2 Sample dependency graph



Note: The GoldenGate agent does not support configurations with a single Extract and multiple DataPump or multiple Replicat values.

You can configure a resource of the GoldenGate type in the `main.cf` file.

Sample main.cf file for an Oracle GoldenGate agent configuration with Oracle PDB

```

include "types.cf"
include "OracleTypes.cf"
include "GoldenGateTypes.cf"

cluster vcspri (
    UserNames = { admin = gJKcJEjGKfKKiSKeJH }
    Administrators = { admin }
    CounterInterval = 5
)

remoteclass vcsdr (
    ClusterAddress = "10.xxx.xx.xx"
)

heartbeat Icmp (

```

```

ClusterList = { vcsdr }
AYARetryLimit = 0
Arguments @vcsdr = { "10.xxx.xx.xx" }
)

system orarep01 (
)

group ClusterService (
    SystemList = { orarep01 = 0 }
    AutoStartList = { orarep01 }
    OnlineRetryLimit = 3
    OnlineRetryInterval = 120
)

Application wac (
    StartProgram = "/opt/VRTSvcs/bin/wacstart"
    StopProgram = "/opt/VRTSvcs/bin/wacstop"
    MonitorProcesses = { "/opt/VRTSvcs/bin/wac" }
)

NIC csgnic (
    Device = eth0
)

wac requires csgnic

group db_OFFFDG (
    SystemList = { orarep01 = 0 }
)

DiskGroup oradg (
    DiskGroup = oradg
)

Netlsnr LSNR_OFFFDG (
    Owner = oracle
    Home = "/opt/oracle/app/oracle/product/11.2.0/Db_1"
    MonScript = "./bin/Netlsnr/LsnrTest.pl"
)

Mount oradb1 (
    MountPoint = "/oradb1"

```

```

        BlockDevice = "/dev/vx/dsk/oradg/oravol"
        FSType = vxfs
        FsckOpt = "-y"
    )

Oracle OFFDG (
    Sid = OFFDG
    Owner = oracle
    Home = "/u01/app/oracle/dbbase/dbhome"
    StartUpOpt = STARTUP
    DBName = OFFDG
)

Oracle OFFDGpdb2_res (
    Sid = OFFDG
    Owner = oracle
    Home = "/u01/app/oracle/dbbase/dbhome"
    StartUpOpt = STARTUP
    PDBName = OFFDGpdb2
)

Oracle OFFDGpdb1_res (
    Sid = OFFDG
    Owner = oracle
    Home = "/u01/app/oracle/dbbase/dbhome"
    StartUpOpt = STARTUP
    PDBName = OFFDGpdb1
)

Volume oravol (
    DiskGroup = oradg
    Volume = oravol
)

OFFDG requires oradb1
OFFDG requires LSNR_OFFDG
oradb1 requires oravol
oravol requires oradg
OFFDGpdb1_res requires OFFDG
OFFDGpdb2_res requires OFFDG

group sw_OFFDG (
    SystemList = { orarep01 = 0 }
)

```

```

ClusterList = { vcspri = 1, vcsdr = 0 }
Authority = 1
ClusterFailOverPolicy = Auto
)

GoldenGate O_goldengate_1 (
  LinkRes = OFFFDG
  GoldenGateHome = "/u01/app/oracle/product/GoldenGate"
  Extract = ext1
  DataPump = dpump1
  Replicat = repl
  AutoTakeover = 0
)

GoldenGate O_goldengate_2 (
  LinkRes = OFFFDG
  GoldenGateHome = "/u01/app/oracle/product/GoldenGate"
  Extract = ext2
  DataPump = dpump2
  Replicat = rep2
  AutoTakeover = 0
)

requires group db_OFFFDG online local hard

```

Before you configure the agent for Oracle GoldenGate

Before you configure the agent, review the following information:

- Verify the hardware setup for the agent.
- Make sure that the cluster has an effective heartbeat mechanism in place.
 - About cluster heartbeats: In a global cluster, VCS sends ICMP pings over the public network between the two sites for network heartbeating. To minimize the risk of split-brain, VCS sends ICMP pings to highly available IP addresses. VCS global clusters also notify the administrators when the sites cannot communicate.
 - About preventing split-brain: Split-brain occurs when all heartbeat links between the primary and secondary hosts are cut. In this situation, each side mistakenly assumes that the other side is down. You can minimize the effects of split-brain by ensuring that the cluster heartbeat links pass through

a similar physical infrastructure as the replication links. When you ensure that both pass through the same infrastructure, if one breaks, so does the other.

- Verify that the clustering infrastructure is in place. If you plan to configure the agent in a global cluster, make sure the global service group for the application is configured.

Configuring the VCS service group for GoldenGate

You can configure the VCS service group for GoldenGate using any of the following methods:

- The Cluster Manager (Java console)
See [“Configuring the VCS service group for GoldenGate using Cluster Manager \(Java console\)”](#) on page 25.
- The command-line
See [“Configuring the VCS service group for GoldenGate using the CLI”](#) on page 26.

Configuring the VCS service group for GoldenGate using Cluster Manager (Java console)

Complete the following procedure to configure a service group in a global cluster.

To configure the service group in a global cluster using Cluster Manager

- 1 Start Cluster Manager and log on to the cluster.
- 2 Add a resource of type GoldenGate at the bottom of the service group.
- 3 Configure the attributes of the GoldenGate resource.
- 4 If the service group is not configured as a global service group, configure the service group using the Global Group Configuration Wizard.
- 5 Repeat steps 2 through 4 for each service group in each cluster that uses replicated data.
- 6 The configuration must be identical on all cluster nodes, both primary and disaster recovery.

Note: You must not change the GoldenGate state of Extract and Replicat outside of a VCS setup. If the role reversal is done externally, the agent for Oracle GoldenGate detects a change in the replication state, but takes no action.

Configuring the VCS service group for GoldenGate using the CLI

Complete the following procedure to configure the service group for GoldenGate using the command-line.

To configure the service group in a global cluster using the command-line

- 1 Configure the value of the LinkRes attribute. This attribute defines the name of the Oracle resource that manages the replicated database instance.

```
# hares -modify ogg_resource_name LinkRes oracle_resource_name
```

The Oracle resource must be online for the GoldenGate resource to come online.

- 2 You may skip this step if the location of the GoldenGate installation directory is `/u01/app/oracle/product/gg`. This location is the default value of the GoldenGateHome attribute.

Configure the value of the GoldenGateHome attribute. This attribute defines the location of the Oracle GoldenGate home directory.

```
# hares -modify ogg_resource_name GoldenGateHome\  
golden_gate_installation_dir
```

Configure this attribute only if the GoldenGate installation directory is not the same as the default value of the attribute.

- 3 Configure the value of the Extract attribute. This attribute defines the name of the local Extract that runs on the system and that the GoldenGate resource monitors.

```
# hares -modify ogg_resource_name Extract local_extract_name
```

- 4 You may skip this step if data pump is not configured.

Configure the value of the DataPump attribute, if data pump is configured. This attribute defines the name of the data pump that the GoldenGate resource monitors.

```
# hares -modify ogg_resource_name DataPump local_datapump_name
```

- 5 Configure the value of the Replicat attribute. This attribute defines the name of the Replicat that the GoldenGate resource monitors.

```
# hares -modify ogg_resource_name Replicat local_replicat_name
```

Managing and testing clustering support for Oracle GoldenGate

This chapter includes the following topics:

- [How VCS recovers from various disasters in an HA/DR setup with Oracle GoldenGate](#)
- [Testing the global service group migration](#)
- [Testing disaster recovery after host failure](#)

How VCS recovers from various disasters in an HA/DR setup with Oracle GoldenGate

When a site-wide global service group or system fault occurs, VCS failover behavior depends on the value of the ClusterFailOverPolicy attribute for the faulted global service group.

The following table lists the failure scenarios in a global cluster configuration and describes the behaviors of VCS and of the agent in response to each failure.

Table 4-1 Failure scenarios in a global cluster configuration with VCS agent for Oracle GoldenGate

Failure	Description and VCS response
Application failure	<p>Application cannot start successfully on any hosts at the primary site.</p> <p>VCS response at the secondary site:</p> <ul style="list-style-type: none"> ■ Causes global service group at the primary site to fault and displays an alert to indicate the fault. ■ Does the following based on the ClusterFailOverPolicy global service group attribute: <ul style="list-style-type: none"> ■ Auto or Connected—VCS automatically brings the faulted global group online at the secondary site. ■ Manual—No action. You must bring the global group online at the secondary site. <p>Agent response:</p> <p>The agent does the following:</p> <ul style="list-style-type: none"> ■ Verifies that all records are processed by Extract and data pump, if configured, in the remote cluster. The remote cluster is the original primary. ■ Stops Extract and data pump, if configured, in the remote cluster. ■ Verifies that local Replicat has processed all records. ■ Stops local Replicat process. ■ Starts local Extract and data pump, if configured.
Host failure	<p>All hosts at the primary site fail.</p> <p>VCS response at the secondary site:</p> <ul style="list-style-type: none"> ■ Displays an alert to indicate the primary cluster fault. ■ Does the following based on the ClusterFailOverPolicy global service group attribute: <ul style="list-style-type: none"> ■ Auto—VCS automatically brings the faulted global group online at the secondary site. ■ Manual or Connected—No action. You must bring the global group online at the secondary site. <p>Agent response:</p> <p>The agent does the following:</p> <ul style="list-style-type: none"> ■ Verifies that local Replicat has processed all records. ■ Agent stops local Replicat process. ■ Starts local Extract and data pump, if configured.

Table 4-1 Failure scenarios in a global cluster configuration with VCS agent for Oracle GoldenGate (*continued*)

Failure	Description and VCS response
Site failure	<p>All hosts and the storage at the primary site fail.</p> <p>VCS response at the secondary site:</p> <ul style="list-style-type: none"> ■ Displays an alert to indicate the cluster fault. ■ Does the following based on the ClusterFailOverPolicy global service group attribute: <ul style="list-style-type: none"> ■ Auto—VCS automatically brings the faulted global group online at the secondary site. ■ Manual or Connected—No action. You must bring the global group online at the secondary site. <p>Agent response:</p> <p>Based on the value of the AutoTakeover attribute, the agent does the following:</p> <ul style="list-style-type: none"> ■ 0-Agent takes no action and the online function exits. ■ 1-Verifies that local Replicat has processed all records. <ul style="list-style-type: none"> ■ Agent stops local Replicat process. ■ Starts local Extract and data pump, if configured.
Network failure	<p>The network connectivity and the replication link between the sites fail. VCS response at the secondary site:</p> <p>Agent response:</p> <p>Based on the value of the AutoTakeover attribute, the agent does the following:</p> <ul style="list-style-type: none"> ■ 0-Takes no action and the online function exits. ■ 1-Verifies that local Replicat has processed all records. <ul style="list-style-type: none"> ■ Stops local Replicat process. ■ Starts local Extract.

Table 4-1 Failure scenarios in a global cluster configuration with VCS agent for Oracle GoldenGate (*continued*)

Failure	Description and VCS response
Storage failure	<p>The array at the primary site fails.</p> <p>VCS response at the secondary site:</p> <ul style="list-style-type: none"> ■ Causes the global service group at the primary site to fault and displays an alert to indicate the fault. ■ Does the following based on the ClusterFailOverPolicy global service group attribute: <ul style="list-style-type: none"> ■ Auto or Connected—VCS automatically brings the faulted global service group online at the secondary site. ■ Manual—No action. You must bring the global group online at the secondary site. <p>Agent response:</p> <p>The agent does the following:</p> <ul style="list-style-type: none"> ■ Verifies that all records are processed by Extract and data pump, if configured, in the remote cluster, which is the original primary. ■ Stops Extract and data pump, if configured, in the remote cluster. ■ Verifies that local Replicat has processed all records. ■ Stops local Replicat process. ■ Starts local Extract and data pump, if configured.

Testing the global service group migration

After you configure the VCS agent for Oracle GoldenGate verify that the global service group can migrate to hosts across the sites.

To test the global service group migration in global cluster setup

- 1 Fail over the global service group from the primary site to the secondary site.

Perform the following steps:

- Switch the global service group from the primary site to any node in the secondary site.

```
hagrps -switch global_group -any -clus cluster_name
```

VCS brings the global service group online on a node at the secondary site.
- Verify that the original primary Extract and data pump, if configured, have processed all records and have stopped.
- Verify that on the secondary site Replicat has processed all records and the Extract and data pump, if configured, have started.

- 2 Fail back the global service group from the secondary site to the primary site.

Perform the following steps:

- Switch the global service group from the secondary site to the primary site.
`hagrp -switch global_group -any -clus cluster_name`
VCS brings the global service group online at the primary site.
- Verify that the Extract and data pump, if configured on the original secondary have processed all records and have stopped.
- Verify that on the original primary site, the Replicat has processed all records and the Extract and data pump, if configured have started.

Testing disaster recovery after host failure

To test disaster recovery for host failure in global cluster setup

- 1 Halt the hosts at the primary site.

The value of the ClusterFailOverPolicy attribute for the faulted global group determines the VCS failover behavior.

- Auto—VCS brings the faulted global service group online at the secondary site.
- Manual or Connected—You must bring the global service group online at the secondary site.

On a node in the secondary site, run the following command:

```
hagrp -online -force global_group -any
```

- 2 Verify that the global service group is online at the secondary site.

```
hagrp -state global_group
```

- 3 Verify that on secondary site Replicat has processed all records and the Extract and data pump, if configured, have started.