

Cluster Server Agent for Informatica PowerCenter Service Manager Installation and Configuration Guide

AIX, HP-UX, Linux, Solaris

7.0

Cluster Server Agent for Informatica PowerCenter Service Manager Installation and Configuration Guide

The software described in this book is furnished under a license agreement and may be used only in accordance with the terms of the agreement.

Agent Version: 7.0

Document version: 7.0 Rev 0

Legal Notice

Copyright © 2016 Veritas Technologies LLC. All rights reserved.

Veritas and the Veritas Logo are trademarks or registered trademarks of Veritas Technologies LLC or its affiliates in the U.S. and other countries. Other names may be trademarks of their respective owners.

This product may contain third party software for which Veritas is required to provide attribution to the third party ("Third Party Programs"). Some of the Third Party Programs are available under open source or free software licenses. The License Agreement accompanying the Software does not alter any rights or obligations you may have under those open source or free software licenses. Please see the Third Party Legal Notice Appendix to this Documentation or TPIP ReadMe File accompanying this product for more information on the Third Party Programs.

The product described in this document is distributed under licenses restricting its use, copying, distribution, and decompilation/reverse engineering. No part of this document may be reproduced in any form by any means without prior written authorization of Veritas Technologies LLC and its licensors, if any.

THE DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID. VERITAS TECHNOLOGIES LLC SHALL NOT BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH THE FURNISHING, PERFORMANCE, OR USE OF THIS DOCUMENTATION. THE INFORMATION CONTAINED IN THIS DOCUMENTATION IS SUBJECT TO CHANGE WITHOUT NOTICE.

The Licensed Software and Documentation are deemed to be commercial computer software as defined in FAR 12.212 and subject to restricted rights as defined in FAR Section 52.227-19 "Commercial Computer Software - Restricted Rights" and DFARS 227.7202, et seq. "Commercial Computer Software and Commercial Computer Software Documentation," as applicable, and any successor regulations, whether delivered by Veritas as on premises or hosted services. Any use, modification, reproduction release, performance, display or disclosure of the Licensed Software and Documentation by the U.S. Government shall be solely in accordance with the terms of this Agreement.

Veritas Technologies LLC
500 E Middlefield Road
Mountain View, CA 94043

<http://www.veritas.com>

Technical Support

Technical Support maintains support centers globally. Technical Support's primary role is to respond to specific queries about product features and functionality. The Technical Support group also creates content for our online Knowledge Base. The Technical Support group works collaboratively with the other functional areas within the company to answer your questions in a timely fashion.

Our support offerings include the following:

- A range of support options that give you the flexibility to select the right amount of service for any size organization
- Telephone and/or Web-based support that provides rapid response and up-to-the-minute information
- Upgrade assurance that delivers software upgrades
- Global support purchased on a regional business hours or 24 hours a day, 7 days a week basis
- Premium service offerings that include Account Management Services

For information about our support offerings, you can visit our website at the following URL:

www.veritas.com/support

All support services will be delivered in accordance with your support agreement and the then-current enterprise technical support policy.

Contacting Technical Support

Customers with a current support agreement may access Technical Support information at the following URL:

www.veritas.com/support

Before contacting Technical Support, make sure you have satisfied the system requirements that are listed in your product documentation. Also, you should be at the computer on which the problem occurred, in case it is necessary to replicate the problem.

When you contact Technical Support, please have the following information available:

- Product release level
- Hardware information
- Available memory, disk space, and NIC information

- Operating system
- Version and patch level
- Network topology
- Router, gateway, and IP address information
- Problem description:
 - Error messages and log files
 - Troubleshooting that was performed before contacting Technical Support
 - Recent software configuration changes and network changes

Licensing and registration

If your product requires registration or a license key, access our technical support Web page at the following URL:

www.veritas.com/support

Customer service

Customer service information is available at the following URL:

www.veritas.com/support

Customer Service is available to assist with non-technical questions, such as the following types of issues:

- Questions regarding product licensing or serialization
- Product registration updates, such as address or name changes
- General product information (features, language availability, local dealers)
- Latest information about product updates and upgrades
- Information about upgrade assurance and support contracts
- Advice about technical support options
- Nontechnical presales questions
- Issues that are related to CD-ROMs, DVDs, or manuals

Support agreement resources

If you want to contact us regarding an existing support agreement, please contact the support agreement administration team for your region as follows:

Worldwide (except Japan)

CustomerCare@veritas.com

Japan

CustomerCare_Japan@veritas.com

Contents

Technical Support	4
Chapter 1 Introducing the agent for Informatica PowerCenter Service Manager	10
About the Cluster Server agent for Informatica PowerCenter Service Manager	10
Supported software	11
Features of the agent	11
How the agent makes Informatica PowerCenter Service Manager highly available	11
High availability for Informatica PowerCenter Service Manager instances running in Solaris zones	12
Informatica PowerCenter Service Manager agent functions	12
Online	12
Offline	13
Monitor	13
Clean	14
Setting up Informatica PowerCenter Service Manager in a VCS cluster	14
Chapter 2 Installing and configuring Informatica PowerCenter Service Manager for high availability	15
About PowerCenter	15
Basic resources to cluster a PowerCenter Service Manager Server	16
Service Group for CFS	16
Service Group for CVM	17
Service Group for PowerCenter Service Manager	17
Virtualizing PowerCenter Service Manager	17

Chapter 3	Installing, upgrading, and removing the agent for Informatica PowerCenter Service Manager	19
	Before you install the Cluster Server agent for Informatica PowerCenter Service Manager	19
	Prerequisites for installing the agent to support Solaris zones	20
	About the ACC library	20
	Installing the ACC library	21
	Installing the ACC library IPS package on Oracle Solaris 11 systems	22
	Installing the ACC library package on Solaris brand non-global zones	22
	Installing the agent in a VCS environment	23
	Installing the agent IPS package on Oracle Solaris 11 systems	25
	Installing agent packages on Solaris brand non-global zones	25
	Installing the agent in a Solaris 10 brand zone	26
	Uninstalling the agent in a VCS environment	27
	Removing the ACC library	28
	Upgrading the agent in a VCS environment	29
Chapter 4	Configuring the agent for Informatica PowerCenter Service Manager	31
	About configuring the Cluster Server agent for Informatica PowerCenter Service Manager	31
	Importing the agent types files in a VCS environment	32
	Changing the default restart behaviour	34
	Informatica PowerCenter Service Manager agent attributes	34
	Executing a customized monitoring program	37
Chapter 5	Configuring the service groups for Informatica PowerCenter Service Manager using the CLI	39
	About configuring service groups for Informatica PowerCenter Service Manager	39
	Before configuring the service groups for Informatica PowerCenter Service Manager	40
	Configuring PowerCenter Service Manager resources for Solaris zones support	40

	Instructing JRE to start running within a “headless” environment	40
Chapter 6	Troubleshooting the agent for Informatica PowerCenter Service Manager	42
	Using the correct software and operating system versions	42
	Meeting prerequisites	43
	Configuring PowerCenter Service Manager resources	43
	Verifying virtualization	43
	Starting the PowerCenter Service Manager instance outside a cluster	43
	Reviewing error log files	44
	Reviewing cluster log files	45
	Using trace level logging	45
Appendix A	Sample Configurations	47
	About sample configurations for the agents for Informatica PowerCenter Service Manager	47
	Sample agent type definition	47
	Sample agent type definition under Solaris zones	48
	Sample configuration	49
	Sample configuration under Solaris zones	53
	Sample service group configurations	57
	Sample service group configuration under Solaris zone	59
Index		62

Introducing the agent for Informatica PowerCenter Service Manager

This chapter includes the following topics:

- [About the Cluster Server agent for Informatica PowerCenter Service Manager](#)
- [Supported software](#)
- [Features of the agent](#)
- [How the agent makes Informatica PowerCenter Service Manager highly available](#)
- [Informatica PowerCenter Service Manager agent functions](#)
- [Setting up Informatica PowerCenter Service Manager in a VCS cluster](#)

About the Cluster Server agent for Informatica PowerCenter Service Manager

Cluster Server (VCS) agents monitor specific resources within an enterprise application. They determine the status of resources and start or stop them according to external events.

The Cluster Server agent for Informatica PowerCenter Service Manager provides high availability for all PowerCenter Service Manager servers in a cluster.

See the Agent Pack Release Notes for the latest updates or software issues for this agent.

Supported software

For information on the software versions that the Cluster Server agent for Informatica PowerCenter Service Manager supports, see the Veritas Services and Operations Readiness Tools (SORT) site: <https://sort.veritas.com/agents>.

Features of the agent

The following are the features of the Cluster Server agent for Informatica PowerCenter Service Manager:

- Support for validation of attributes that are based on the agent functions
The agent can validate attributes in each agent function before the actual data processing starts.
- Support for First Failure Data Capture (FFDC)
In case of a fault, the agent generates a huge volume of the debug logs that enable troubleshooting of the fault.
- Support for Fast First Level Monitor (FFLM)
The agent maintains PID files based on search patterns to expedite the monitoring process.
- Support for external user-supplied monitor utilities
The agent enables user-specified monitor utilities to be plugged in, in addition to the built-in monitoring logic. This enables administrators to completely customize the monitoring of the application.
- Delayed agent function
The agent manages the first monitor after online for slow initializing applications.

How the agent makes Informatica PowerCenter Service Manager highly available

The agent provides the following levels of application monitoring:

- Primary or Basic monitoring
This mode has Process check and Health check monitoring options. With the default Process check option, the agent verifies that the PowerCenterSvcMgr instance processes are present in the process table. Process check cannot detect whether processes are in the hung or stopped states.
- Secondary or Detail monitoring
In this mode, the agent runs a utility to verify the status of the PowerCenterSvcMgr instance. The agent detects application failure if the

monitoring routine reports an improper function of the PowerCenterSvcMgr instance processes. When this application failure occurs, the PowerCenterSvcMgr instance service group fails over to another node in the cluster.

Thus, the agent ensures high availability for PowerCenterSvcMgr instances.

High availability for Informatica PowerCenter Service Manager instances running in Solaris zones

Solaris provides a means of virtualizing operating system services, allowing one or more processes to run in isolation from other activity on the system. Such a 'sandbox' is called a 'non-global zone'. Each zone can provide a rich and customized set of services. The processes that run in a 'global zone' have the same set of privileges that are available on a Solaris system today.

VCS provides high availability to applications running in non-global zones by extending the failover capability to zones. VCS is installed in a global zone, and all the agents and the engine components run in the global zone. For applications running within non-global zones, agents run script entry points inside the zones. If a zone configured under VCS control faults, VCS fails over the entire service group containing the zone.

For more details, refer to the *Cluster Server Administrator's Guide*.

The Cluster Server agent for Informatica PowerCenter Service Manager is zone-aware and can monitor PowerCenterSvcMgr instances running in non-global zones.

Informatica PowerCenter Service Manager agent functions

The agent consists of resource type declarations and agent executables. The agent executables implement the online, offline, monitor and clean operations.

Online

The online operation performs the following tasks:

- Verifies that the required attributes are set correctly.
- Verifies whether the PowerCenter Service Manager Server instance is not ready online. If the instance is online, the online operation exits immediately.
- Kills the PowerCenter Service Manager processes that remain online using the login associated with the specific resource.

- Executes the following command, in context of InfaUser to start the PowerCenter Service Manager instance:

```
$ InfaHome/Server/tomcat/bin/infaservice.sh startup
```

- Verifies whether the PowerCenter Service Manager Server is completely functional.
- Returns the control to HAD.

Offline

The offline operation performs the following tasks:

- Verifies that the required attributes are set correctly.
- Verifies whether the PowerCenter Service Manager Server instance is not offline. If found, the operation kills any existing processes that belong to this instance of PowerCenter Service Manager being clustered, and exits.
- Executes the following command, in context of InfaUser to stop the PowerCenter Service Manager Server instance.

```
$ InfaHome/Server/tomcat/bin/infaservice.sh shutdown
```

- Kills any existing processes that belong to this instance of PowerCenter Service Manager Server after the offline script is executed.
- Returns the control to HAD.

Monitor

The monitor operation performs the states of the PowerCenter Service Manager Servers on all nodes within the cluster.

The operation performs the following tasks:

- Conducts a first level check to determine that the PowerCenter Service Manager Server processes that the user specified in the PowerCenterSvcMgr agent attribute, are running on the system in the cluster. If the first level check does not find these processes running on the node, the check exits immediately, and reports the instance as offline.
- Conducts a second level check if the SecondLevelMonitor attribute is set to a value greater than 0.
- Uses a connect (3c) method to check for the PowerCenter Service Manager Server to listen to the port defined by the Port attribute. The host name needed to perform this check is derived from the InfaHome agent attribute.
- Depending upon the MonitorProgram attribute, the monitor operation performs a customized check using a user-supplied monitoring utility.

See [“Executing a customized monitoring program”](#) on page 37.

Clean

The clean operation performs the following tasks in the event of a failure or an unsuccessful attempt to bring a PowerCenter Service Manager Server instance online or take it offline:

- Attempts to gracefully shut down the PowerCenter Service Manager Server instance, using the following command in context of InfaUser.
`$ InfaHome/Server/tomcat/bin/infaservice.sh shutdown`
- Kills the remaining processes pertaining to this PowerCenter Service Manager Server if the instance does not shut down normally.
- Returns the control to HAD.

Note: By default the agent attempts to restart a faulted resource 1000 times before the resource is marked as faulted.

See [“Changing the default restart behaviour”](#) on page 34.

Setting up Informatica PowerCenter Service Manager in a VCS cluster

Follow the steps below to set up Informatica PowerCenter Service Manager in a cluster:

- Set up a VCS cluster.
 For more information on installing and configuring Cluster Server, refer to the Cluster Server installation and configuration guides.
- Install and configure Informatica PowerCenter Service Manager for High Availability.
 See [“About configuring the Cluster Server agent for Informatica PowerCenter Service Manager”](#) on page 31.
- Install the Cluster Server agent for Informatica PowerCenter Service Manager.
 See [“Installing the agent in a VCS environment”](#) on page 23.
- Configure the service groups for Informatica PowerCenter Service Manager.
 See [“About configuring service groups for Informatica PowerCenter Service Manager”](#) on page 39.
- Enable the Tomcat “headless” process for Informatica PowerCenter 8.1.1.

Installing and configuring Informatica PowerCenter Service Manager for high availability

This chapter includes the following topics:

- [About PowerCenter](#)
- [Basic resources to cluster a PowerCenter Service Manager Server](#)
- [Virtualizing PowerCenter Service Manager](#)

About PowerCenter

Informatica PowerCenter, is a single and unified enterprise data intergration platform, that enables you to access and intergrate data from a business system.

Key features of Informatica PowerCenter include the following:

- Data migration
- Data synchronization
- Enterprise data warehousing
- Master data management
- Cross-enterprise data integration
- Data governance

- Service-oriented architectures
- Integration competency centers
- Universal data access
- Mission-critical and Enterprise-wide data integration

PowerCenter is available in the following editions:

- PowerCenter Standard Edition
- PowerCenter Real Time Edition
- PowerCenter Advance Edition

Basic resources to cluster a PowerCenter Service Manager Server

A cluster setup for PowerCenter Service Manager, is split into the following three service groups:

- Cluster Filesystem (CFS)
- Cluster Volume Manager (CVM)
- PowerCenter Service Manager

The PowerCenter Service Manager resources depend on the resources of CFS and CVM service groups, for the prerequisite disk groups, volumes and mount points.

The recommended resources and its setup for each of the above service groups are described in the following subsections.

For information on the service group dependencies,

See [“Sample service group configurations”](#) on page 57.

Service Group for CFS

The CFS service group has the following resources:

- CVM Volume Diskgroup
The CVM disk groups provide an active/active clustered set of volumes that are used to create the CFS, that is mounted in parallel on all configured nodes.
Use the CVMVolDg resource type to create this resource.
- CFS Mount

This resource is used to provide the CFS active/active shared file system to PowerCenter infa_shared objects from \$PMROOTDir directory. Such directories include Cache, Storage, SrcFiles, TgtFiles etc.

You can also use this resource to place the Informatica PowerCenter binaries on the shared CFS.

Use the CFSMount resource type to create this resource.

Service Group for CVM

The CVM service group has the following resources.

- CFSfsckd
The CFSfsckd resource is used to start the cluster file system check (using the `fsck` command), daemon, and vxfsckd that runs for a cluster mount to succeed. Use the CFSfsckd resource type to create this resource.
- CVMCluster
The CVMCluster resource controls the overall operation of CVM. The agents of CVMCluster bring up the CVM cluster. Use the CVMCluster resource type to create this resource.
- CVMVxconfigd
The vxconfigd daemon maintains disk and disk group configurations, communicates configuration changes to the kernel, and modifies configuration information stored on the disks. CVMVxconfigd is required in the Cluster Volume Manager service group to start and monitor the vxconfigd daemon. Use the CVMVxconfigd resource type to create this resource.

Service Group for PowerCenter Service Manager

The PowerCenter Service Manager service group contains the Informatica PowerCenter Service Manager resource. This resource starts, stops and monitors the Informatica PowerCenter Service Manager instance. Once the Service Manager is either stopped or started, this resource manages all the subordinate Informatica PowerCenter processes and services within its service framework.

Use the PowerCenterSvcMgr resource type to create this resource.

Virtualizing PowerCenter Service Manager

To ensure that your Service Manager Server can function properly on any node of the cluster, you need to virtualize all the parameters that could be dependent on a particular node.

Review the following basic notes for virtualization:

Host names	When installing and configuring the Service Manager Server, ensure that you enter the virtual host name associated with the IP address used to configure the IP resource. This ensures that if the application needs to be migrated, you are not tied down by the physical IP address given to the Service Manager Server.
Path names	Ensure that your application gets installed on a shared disk so that it is not constrained by anything that is local to the node. If this is not possible every time, make sure that the local data is available on each configured node.

Installing, upgrading, and removing the agent for Informatica PowerCenter Service Manager

This chapter includes the following topics:

- [Before you install the Cluster Server agent for Informatica PowerCenter Service Manager](#)
- [About the ACC library](#)
- [Installing the ACC library](#)
- [Installing the agent in a VCS environment](#)
- [Uninstalling the agent in a VCS environment](#)
- [Removing the ACC library](#)
- [Upgrading the agent in a VCS environment](#)

Before you install the Cluster Server agent for Informatica PowerCenter Service Manager

You must install the Cluster Server agent for Informatica PowerCenter Service Manager on all the systems that will host PowerCenter Service Manager service groups.

Before you install the agent for Informatica PowerCenter Service Manager, ensure that the following prerequisites are met.

- Install and configure Cluster Server.
For more information on installing and configuring Cluster Server, refer to the Cluster Server installation and configuration guides.
- Remove any previous version of this agent.
To remove the agent,
See [“Uninstalling the agent in a VCS environment”](#) on page 27.
- Install the latest version of ACC Library.
To install or update the ACC Library package, locate the library and related documentation in the Agent Pack tarball,
See [“Installing the ACC library”](#) on page 21.

Prerequisites for installing the agent to support Solaris zones

Ensure that you meet the following prerequisites to install the agent for Informatica PowerCenter Service Manager:

- Install PowerCenter Service Manager to support Solaris zones. For details refer to Informatica user documentation.
- Install and configure the VCS environment to support Solaris zones. Refer to the VCS user documentation for details.
- Install the required version of ACC Library.
- Remove any previous version of this agent.

About the ACC library

The operations of a Cluster Server agent depend on a set of Perl modules known as the ACC library. The library must be installed on each system in the cluster that runs the agent. The ACC library contains common, reusable functions that perform tasks, such as process identification, logging, and system calls.

Instructions to install or remove the ACC library on a single system in the cluster are given in the following sections. The instructions assume that the ACCLib tar file has already been extracted.

Note: The LogDbg attribute should be used to enable debug logs for the ACCLib-based agents when the ACCLib version is 6.2.0.0 or later and VCS version is 6.2 or later.

Installing the ACC library

Install the ACC library on each system in the cluster that runs an agent that depends on the ACC library.

To install the ACC library

- 1 Log in as a superuser.
- 2 Download ACC Library.

You can download either the complete Agent Pack tar file or the individual ACCLib tar file from the Veritas Services and Operations Readiness Tools (SORT) site (<https://sort.veritas.com/agents>).

- 3 If you downloaded the complete Agent Pack tar file, navigate to the directory containing the package for the platform running in your environment.

AIX	<code>cd1/aix/vcs/application/acc_library/version_library/pkgs</code>
HP-UX	<code>cd1/hpux/generic/vcs/application/acc_library/version_library/pkgs</code>
Linux	<code>cd1/linux/generic/vcs/application/acc_library/version_library/rpms</code>
Solaris	<code>cd1/solaris/dist_arch/vcs/application/acc_library/version_library/pkgs</code> where <code>dist_arch</code> is <code>sol_sparc</code> .

- 4 If you downloaded the individual ACCLib tar file, navigate to the `pkgs` directory (for AIX and Solaris), or `rpms` directory (for Linux).
- 5 Install the package. Enter **Yes**, if asked to confirm overwriting of files in the existing package.

AIX	<code># installp -ac -d VRTSaccclib.bff VRTSaccclib</code>
HP-UX	<code># swinstall -s 'pwd' VRTSaccclib</code>
Linux	<code># rpm -i \ VRTSaccclib-VersionNumber-GA_GENERIC.noarch.rpm</code>
Solaris	<code># pkgadd -d VRTSaccclib.pkg</code>

Note: The `LogDbg` attribute should be used to enable debug logs for the ACCLib-based agents when the ACCLib version is 6.2.0.0 or later and VCS version is 6.2 or later.

Installing the ACC library IPS package on Oracle Solaris 11 systems

Install the ACC library IPS package on an Oracle Solaris 11 system.

To install the ACC library IPS package on Oracle Solaris 11 systems

- 1 Copy the `VRTSaccplib.p5p` package from the `pkgs` directory to the system in the `/tmp/install` directory.

- 2 Disable the publishers that are not reachable as package install may fail, if any, of the already added repositories are unreachable.

```
# pkg set-publisher --disable <publisher name>
```

- 3 Add a file-based repository in the system.

```
# pkg set-publisher -g /tmp/install/VRTSaccplib.p5p Symantec
```

- 4 Install the package.

```
# pkg install --accept VRTSaccplib
```

- 5 Remove the publisher from the system.

```
# pkg unset-publisher Symantec
```

- 6 Enable the publishers that were disabled earlier.

```
# pkg set-publisher --enable <publisher name>
```

Installing the ACC library package on Solaris brand non-global zones

With Oracle Solaris 11, you must install the ACC library package inside non-global zones. The native non-global zones are called Solaris brand zones.

To install the ACC library package on Solaris brand non-global zones

- 1 Ensure that the SMF services,
`svc:/application/pkg/system-repository:default` and
`svc:/application/pkg/zones-proxyd:default`, are online on the global zone.

```
# svcs svc:/application/pkg/system-repository:default
```

```
# svcs svc:/application/pkg/zones-proxyd:default
```

- 2 Log on to the non-global zone as a superuser.

- 3 Ensure that the SMF service
`svc:/application/pkg/zones-proxy-client:default` is online inside the non-global zone:

```
# svcs svc:/application/pkg/zones-proxy-client:default
```

- 4 Copy the `VRTSacclib.p5p` package from the `pkgs` directory to the non-global zone (for example, at the `/tmp/install` directory).
- 5 Disable the publishers that are not reachable, as package install may fail, if any of the already added repositories are unreachable.

```
# pkg set-publisher --disable <publisher name>
```
- 6 Add a file-based repository in the non-global zone.

```
# pkg set-publisher -g/tmp/install/VRTSacclib.p5p Symantec
```
- 7 Install the package.

```
# pkg install --accept VRTSacclib
```
- 8 Remove the publisher on the non-global zone.

```
# pkg unset-publisher Symantec
```
- 9 Clear the state of the SMF service, as setting the file-based repository causes the SMF service `svc:/application/pkg/system-repository:default` to go into the maintenance state.

```
# svcadm clear svc:/application/pkg/system-repository:default
```
- 10 Enable the publishers that were disabled earlier.

```
# pkg set-publisher --enable <publisher>
```

Note: Perform steps 2 through 10 on each non-global zone.

Installing the agent in a VCS environment

Install the agent for Informatica PowerCenter Service Manager on each node in the cluster.

To install the agent in a VCS environment

- 1 Download the agent from the Veritas Services and Operations Readiness Tools (SORT) site: <https://sort.veritas.com/agents>.

You can download either the complete Agent Pack tar file or an individual agent tar file.
- 2 Uncompress the file to a temporary location, say `/tmp`.

- 3 If you downloaded the complete Agent Pack tar file, navigate to the directory containing the package for the platform running in your environment.

AIX	<code>cd1/aix/vcs/application/powercentersvcmgr_agent/ vcs_version/version_agent/pkg</code>
HP-UX	<code>cd1/hpux/generic/vcs/application/powercentersvcmgr_agent/ vcs_version/version_agent/pkg</code>
Linux	<code>cd1/linux/generic/vcs/application/powercentersvcmgr_agent/ vcs_version/version_agent/rpm</code>
Solaris	<code>cd1/solaris/dist_arch/vcs/application/powercentersvcmgr_agent/ vcs_version/version_agent/pkg</code> where, <i>dist_arch</i> is sol_sparc.

If you downloaded the individual agent tar file, navigate to the pkg directory (for AIX and Solaris), or rpm directory (for Linux).

- 4 Log in as a superuser.
- 5 Install the package.

AIX	<code># installp -ac -d VRTSpvcsmgr.rte.bff VRTSpvcsmgr.rte</code>
HP-UX	<code># swinstall -s 'pwd' VRTSpvcsmgr</code>
Linux	<code># rpm -ihv \ VRTSpvcsmgr-AgentVersion-GA_GENERIC.noarch.rpm</code>
Solaris	<code># pkgadd -d . VRTSpvcsmgr</code>

- 6 After installing the agent package, you must import the agent type configuration file.

Installing the agent IPS package on Oracle Solaris 11 systems

To install the agent IPS package on an Oracle Solaris 11 system

- 1 Disable the publishers that are not reachable as package install may fail, if any of the already added repositories are unreachable.

```
# pkg set-publisher --disable <publisher name>
```

where the publisher name is obtained using the `pkg publisher` command.

- 2 Add a file-based repository in the system.

```
# pkg set-publisher -g /tmp/install/VRTSpcsvcmgr.p5p Symantec
```

- 3 Install the package.

```
# pkg install --accept VRTSpcsvcmgr
```

- 4 Remove the publisher from the system.

```
# pkg unset-publisher Symantec
```

- 5 Enable the publishers that were disabled earlier.

```
# pkg set-publisher --enable <publisher name>
```

Installing agent packages on Solaris brand non-global zones

With Oracle Solaris 11, you must install the agent package inside non-global zones. The native non-global zones are called Solaris brand zones.

To install the agent package on Solaris brand non-global zones

- 1 Ensure that the SMF services,
`svc:/application/pkg/system-repository:default` and
`svc:/application/pkg/zones-proxyd:default`, are online on the global zone.

```
# svcs svc:/application/pkg/system-repository:default
```

```
# svcs svc:/application/pkg/zones-proxyd:default
```

- 2 Log on to the non-global zone as a superuser.

- 3 Ensure that the SMF service
`svc:/application/pkg/zones-proxy-client:default` is online inside non-global zone:

```
# svcs svc:/application/pkg/zones-proxy-client:default
```

- 4 Copy the `VRTSpcsvcmgr.p5p` package from the `pkgs` directory to the non-global zone (for example, at the `/tmp/install` directory).

- 5 Disable the publishers that are not reachable, as package install may fail, if any of the already added repositories are unreachable.

```
# pkg set-publisher --disable <publisher name>
```

- 6 Add a file-based repository in the non-global zone.

```
# pkg set-publisher -g/tmp/install/VRTSpcsvcmgr.p5p Symantec
```

- 7 Install the package.

```
# pkg install --accept VRTSpcsvcmgr
```

- 8 Remove the publisher on the non-global zone.

```
# pkg unset-publisher Symantec
```

- 9 Clear the state of the SMF service, as setting the file-based repository causes the SMF service `svc:/application/pkg/system-repository:default` to go into the maintenance state.

```
# svcadm clear svc:/application/pkg/system-repository:default
```

- 10 Enable the publishers that were disabled earlier.

```
# pkg set-publisher --enable <publisher>
```

Note: Perform steps 2 through 10 on each non-global zone.

Installing the agent in a Solaris 10 brand zone

To install the Informatica PowerCenter Service Manager agent in a Solaris 10 brand zone:

- Ensure that the ACC library package, `VRTSaclib`, is installed in the non-global zone.

To install `VRTSaclib` in the non-global zone, run the following command from the global zone:

```
# pkgadd -R /zones/zone1/root -d VRTSaclib.pkg
```

- To install the agent package in the non-global zone, run the following command from the global zone:

```
# pkgadd -R zone-root/root -d . VRTSpcsvcmgr
```

For example: `# pkgadd -R /zones/zone1/root -d . VRTSpcsvcmgr`

Uninstalling the agent in a VCS environment

You must uninstall the agent for Informatica PowerCenter Service Manager from a cluster while the cluster is active.

To uninstall the agent in a VCS environment

- 1 Log in as a superuser.
- 2 Set the cluster configuration mode to read/write by running the following command from any node in the cluster:

```
# haconf -makerw
```

- 3 Remove all PowerCenter Service Manager resources from the cluster. Run the following command to verify that all resources have been removed:

```
# hares -list Type=PowerCenterSvcMgr
```

- 4 Remove the agent type from the cluster configuration by running the following command from any node in the cluster:

```
# hatype -delete PowerCenterSvcMgr
```

Removing the agent's type file from the cluster removes the include statement for the agent from the `main.cf` file, but the agent's type file is not removed from the cluster configuration directory. You can remove the agent's type file later from the cluster configuration directory.

- 5 Save these changes. Then set the cluster configuration mode to read-only by running the following command from any node in the cluster:

```
# haconf -dump -makero
```

- 6 Use the platform's native software management program to remove the agent for Informatica PowerCenter Service Manager from each node in the cluster.

Run the following command to uninstall the agent:

AIX `# installp -u VRTSpcsvcmgr.rte`

HP-UX `# swremove VRTSpcsvcmgr`

Linux `# rpm -e VRTSpcsvcmgr`

Solaris `# pkgrm VRTSpcsvcmgr`

Note: To uninstall the agent IPS package on a Solaris 11 system, run the following command:

```
# pkg uninstall VRTSpcsvcmgr
```

Removing the ACC library

Perform the following steps to remove the ACC library.

To remove the ACC library

- 1 Ensure that all agents that use ACC library are removed.
- 2 Run the following command to remove the ACC library package:

AIX `# installp -u VRTSacclib`

HP-UX `# swremove VRTSacclib`

Linux `# rpm -e VRTSacclib`

Solaris `# pkgrm VRTSacclib`

Note: To uninstall the ACCLib IPS package on a Solaris 11 system, run the following command:

```
# pkg uninstall VRTSacclib
```

Upgrading the agent in a VCS environment

Perform the following steps to upgrade the agent with minimal disruption, in a VCS environment.

To upgrade the agent in a VCS environment

- 1 Persistently freeze the service groups that host the application.

```
# hagr -freeze GroupName -persistent
```

- 2 Stop the cluster services forcibly.

```
# hstop -all -force
```

- 3 Ensure that the agent operations are stopped on all the nodes.

```
# ps -ef | grep PowerCenterSvcMgr
```

- 4 Uninstall the agent package from all the nodes. Use the platform's native software management program to remove the agent for Informatica PowerCenter Service Manager from each node in the cluster.

Run the following command to uninstall the agent:

```
AIX # installp -u VRTSpcsvcmgr.rte
```

```
HP-UX # swremove VRTSpcsvcmgr
```

```
Linux # rpm -e VRTSpcsvcmgr
```

Solaris For Solaris 10:

```
# pkgrm VRTSpcsvcmgr
```

For Solaris 11:

```
# pkg uninstall VRTSpcsvcmgr
```

- 5 Install the new agent on all the nodes.

See [“Installing the agent in a VCS environment”](#) on page 23.

- 6 Copy the new `PowerCenterSvcMgrTypes.cf` file from the agent's conf directory, to the VCS conf directory `/etc/VRTSvcs/conf/config`.

VCS 4.x	<ul style="list-style-type: none"> ■ AIX ■ HP-UX ■ Linux ■ Solaris 	/etc/VRTSvcs/conf/sample_PowerCenterSvcMgr/ PowerCenterSvcMgrTypes.cf
VCS 5.x or later	<ul style="list-style-type: none"> ■ AIX ■ HP-UX ■ Linux 	/etc/VRTSagents/ha/conf/PowerCenterSvcMgr/ PowerCenterSvcMgrTypes.cf
VCS 5.0	<ul style="list-style-type: none"> ■ Solaris SPARC 	/etc/VRTSagents/ha/conf/PowerCenterSvcMgr/ PowerCenterSvcMgrTypes50.cf
VCS 5.1 or later	<ul style="list-style-type: none"> ■ Solaris SPARC 	/etc/VRTSagents/ha/conf/PowerCenterSvcMgr/ PowerCenterSvcMgrTypes51.cf

Note: If you are using Solaris SPARC, copy the `PowerCenterSvcMgrTypes50.cf` file for VCS 5.0 (and its intermediate Maintenance Packs) and `PowerCenterSvcMgrTypes51.cf` file for VCS 5.1 or later.

- 7 Check for the changes in the resource values required, if any, due to the new agent types file.

Note: To note the list of changed attributes, compare the new type definition file with the old type definition file.

- 8 Start the cluster services.

```
# hstart
```

- 9 Start the agent on all nodes, if not started.

```
# haagent -start PowerCenterSvcMgr -sys SystemName
```

- 10 Unfreeze the service groups once all the resources come to an online steady state.

```
# hagrps -unfreeze GroupName -persistent
```

Configuring the agent for Informatica PowerCenter Service Manager

This chapter includes the following topics:

- [About configuring the Cluster Server agent for Informatica PowerCenter Service Manager](#)
- [Importing the agent types files in a VCS environment](#)
- [Changing the default restart behaviour](#)
- [Informatica PowerCenter Service Manager agent attributes](#)
- [Executing a customized monitoring program](#)

About configuring the Cluster Server agent for Informatica PowerCenter Service Manager

After installing the Cluster Server agent for Informatica PowerCenter Service Manager, you must import the agent type configuration file. After importing this file, review the attributes table that describes the resource type and its attributes, and then create and configure PowerCenter Service Manager resources.

To view the sample agent type definition and service groups configuration:

See [“About sample configurations for the agents for Informatica PowerCenter Service Manager”](#) on page 47.

Importing the agent types files in a VCS environment

To use the agent for Informatica PowerCenter Service Manager, you must import the agent types file into the cluster.

You can import the agent types file using the VCS graphical user interface or using the command line interface.

To import the agent types file using the VCS graphical user interface

- 1
- Start the Cluster Manager (Java Console) and connect to the cluster on which the agent is installed.
- 2
- Click **File > Import Types**.
- 3
- In the **Import Types** dialog box, select the following file:

VCS 4.x	■ AIX	/etc/VRTSvcs/conf/sample_PowerCenterSvcMgr/
	■ HP-UX	PowerCenterSvcMgrTypes.cf
	■ Linux	
	■ Solaris	
VCS 5.x or later	■ AIX	/etc/VRTSagents/ha/conf/PowerCenterSvcMgr/
	■ HP-UX	PowerCenterSvcMgrTypes.cf
	■ Linux	
VCS 5.0	Solaris SPARC	/etc/VRTSagents/ha/conf/PowerCenterSvcMgr/
		PowerCenterSvcMgrTypes50.cf
VCS 5.1 or later	Solaris SPARC	/etc/VRTSagents/ha/conf/PowerCenterSvcMgr/
		PowerCenterSvcMgrTypes51.cf

- 4
- Click **Import**.
- 5
- Save the VCS configuration.

The PowerCenter Service Manager agent type is now imported to the VCS engine.

You can now create PowerCenter Service Manager resources. For additional information about using the VCS GUI, refer to the *Cluster Server Administrator's Guide*.

To import the agent types file using the command line interface (CLI):

- 1** Log on to any one of the systems in the cluster as the superuser.
- 2** Create a temporary directory.

```
# mkdir ./temp

# cd ./temp
```

- 3** Copy the sample file `Types.cf`.

VCS 4.x	<ul style="list-style-type: none"> ■ AIX <code>/etc/VRTSvcs/conf/sample_PowerCenterSvcMgr/</code> ■ HP-UX <code>PowerCenterSvcMgrTypes.cf</code> ■ Linux ■ Solaris
VCS 5.x or later	<ul style="list-style-type: none"> ■ AIX <code>/etc/VRTSagents/ha/conf/PowerCenterSvcMgr/</code> ■ HP-UX <code>PowerCenterSvcMgrTypes.cf</code> ■ Linux
VCS 5.0	<ul style="list-style-type: none"> ■ Solaris SPARC <code>/etc/VRTSagents/ha/conf/PowerCenterSvcMgr/</code> <code>PowerCenterSvcMgrTypes50.cf</code>
VCS 5.1 or later	<ul style="list-style-type: none"> ■ Solaris SPARC <code>/etc/VRTSagents/ha/conf/PowerCenterSvcMgr/</code> <code>PowerCenterSvcMgrTypes51.cf</code>

The following example assumes VCS 5.0 is installed on AIX:

```
# cp \
/etc/VRTSagents/ha/conf/PowerCenterSvcMgr/PowerCenterSvcMgrTypes.cf .
```

4 Create a dummy `main.cf` file.

```
# echo 'include "PowerCenterSvcMgrTypes.cf"' > main.cf
```

5 Create the `PowerCenterSvcMgr` resource type as follows:

```
# hacf -verify .  
  
# haconf -makerw  
  
# sh main.cmd  
  
# haconf -dump
```

The PowerCenter Service Manager agent type is now imported to the VCS engine.

You can now create PowerCenter Service Manager resources. For additional information about using the VCS CLI, refer to the *Cluster Server Administrator's Guide*.

Changing the default restart behaviour

The agent by default attempts to restart a faulted PowerCenter Service Manager resource 1000 times before it faults.

To change this default behaviour, execute the following commands:

```
# haconf -makerw  
# hatype -modify PowerCenterSvcMgr RestartLimit RestartLimit  
# haconf -dump
```

where, *RestartLimit* represents the value for the number of times VCS must restart the faulted PowerCenter Service Manager resource, before executing the clean function.

Informatica PowerCenter Service Manager agent attributes

Refer to the required and optional attributes while configuring the agent for Informatica PowerCenter Service Manager.

[Table 4-1](#) lists the required attributes for the Informatica PowerCenter Service Manager agent.

Table 4-1 Required attributes

Required attributes	Description
ResLogLevel	<p>Specifies the logging detail performed by the agent for the resource.</p> <p>The valid values are as follows:</p> <ul style="list-style-type: none"> ■ ERROR: Only logs error messages. ■ WARN: Logs above plus warning messages. ■ INFO: Logs above plus informational messages. ■ TRACE: Logs above plus trace messages. TRACE is very verbose and should only be used during initial configuration or for troubleshooting and diagnostic operations. <p>Default: INFO</p> <p>Example: INFO</p>
InfaUser	<p>Specifies the account name under which the agent executes programs to manage the Service Manager.</p> <p>Default: ""</p> <p>Example: infaPC</p>
EnvFile	<p>Specifies the full path to the file that the agent sources use to set the environment before executing any Service Manager programs. This attribute should be set as a local attribute and should point to a unique environment file on each configured node.</p> <p>Veritas recommends to create this file preferably in the InfaHome directory.</p> <p>The supported shell environments are: Bourne, Korn, and C shell.</p> <p>Default: ""</p> <p>Example,</p> <p>On nodeA: /u01/app/infa_bin/PowerCenter/nodeA/envfile</p> <p>On nodeB: /u01/app/infa_bin/PowerCenter/nodeB/envfile</p>
Port	<p>Represents the port number dedicated for the PowerCenter Administration Console. The monitor agent function uses this value to determine if the console responds to HTTP requests.</p> <p>This is a required attribute only if SecondLevelMonitor is enabled.</p> <p>Default: 6001</p> <p>Example: 6001</p>

Table 4-1 Required attributes (*continued*)

Required attributes	Description
InfaHome	<p>Represents the Service Manager installation directory.</p> <p>Default: ""</p> <p>Examples:</p> <p>On nodeA: /u01/app/infa_bin/PowerCenter/nodeA</p> <p>On nodeB: /u01/app/infa_bin/PowerCenter/nodeB</p>
HostName	<p>Specifies the IPv4 address or host name of the virtual host which is configured for the Informatica PowerCenter instance. This attribute should be set as a local attribute on each configured node.</p> <p>Default: ""</p> <p>Examples:</p> <p>On nodeA: pwrsvcmgr-01</p> <p>On nodeB: pwrsvcmgr-02</p> <p>Where, pwrsvcmgr-01 and pwrsvcmgr-02 are the virtual hosts configured for hosting the PowerCenter Service Manager resources on nodeA and nodeB respectively.</p>

[Table 4-2](#) lists the optional attributes for the PowerCenterSvcMgr agent.

Table 4-2 Optional attributes

Optional attributes	Description
MonitorProgram	<p>Absolute path name of an external, user-supplied monitor executable. If specified, the monitor function executes this file to perform an additional state check of the server. There are no restrictions for what actions the external monitor program performs to determine the state of the server.</p> <p>For information about setting this attribute:</p> <p>See “Executing a customized monitoring program” on page 37.</p> <p>Default: ""</p> <p>Example 1: /u01/app/infa_bin/PowerCenter/nodeA/bin/monitor.sh</p> <p>Example 2: /u01/app/infa_bin/PowerCenter/nodeB/bin/monitor.pl <i>arg1 arg2</i></p>

Table 4-2 Optional attributes (*continued*)

Optional attributes	Description
SecondLevelMonitor	<p>Used to enable second-level monitoring. Second-level monitoring is a deeper, more thorough state check of the Service Manager. The numeric value specifies how often the monitoring routines must run. 0 means never run the second-level monitoring routines, 1 means run routines every monitor interval, 2 means run routines every second monitor interval. This interpretation may be extended to other values.</p> <p>Note: Exercise caution while setting SecondLevelMonitor to large numbers. For example, if the MonitorInterval is set to 60 seconds and the SecondLevelMonitor is set to 100, then the second level check is executed every 100 minutes, which may not be as often as intended. For maximum flexibility, no upper limit is defined for SecondLevelMonitor.</p> <p>Default: 0</p> <p>Example: 1</p>

Executing a customized monitoring program

You can configure the monitor function to execute a custom monitor utility to perform a user-defined Service Manager Server state check. The utility is executed in the context of the UNIX user that is defined in the InfaUser attribute. The environment is set by sourcing the file specified in the EnvFile attribute.

The monitor function executes the utility specified in the MonitorProgram attribute if the following conditions are satisfied:

- The MonitorProgram attribute value is set to a valid executable utility.
- The first-level process check indicates that the PowerCenter Service Manager instance is online.
- The SecondLevelMonitor attribute is set to 1 and the second-level check returns the server state as "online" or the SecondLevelMonitor attribute is set to a value greater than 1, but the second-level check is deferred for this monitoring cycle.

The monitor function interprets the program exit code as follows:

- | | |
|----------|--|
| 110 or 0 | Service Manager Server instance is online |
| 100 or 1 | Service Manager Server instance is offline |

Any other Service Manager Server instance is unknown
value

To ensure that the custom monitor utility is always available to the agent, Veritas recommends storing the file in the directory where the Service Manager Server is installed.

Configuring the service groups for Informatica PowerCenter Service Manager using the CLI

This chapter includes the following topics:

- [About configuring service groups for Informatica PowerCenter Service Manager](#)
- [Before configuring the service groups for Informatica PowerCenter Service Manager](#)
- [Configuring PowerCenter Service Manager resources for Solaris zones support](#)
- [Instructing JRE to start running within a “headless” environment](#)

About configuring service groups for Informatica PowerCenter Service Manager

Configuring the Informatica PowerCenter Service Manager service group involves creating the PowerCenter Service Manager service group, its resources, and defining attribute values for the configured resources. You must have administrator privileges to create and configure a service group.

You can configure the service groups using one of the following:

- The Cluster Manager (Java console)
- Veritas Infoscale Operations Manager

- The command line

Before configuring the service groups for Informatica PowerCenter Service Manager

Before you configure the PowerCenter Service Manager service group, you must:

- Verify that Cluster Server is installed and configured on all nodes in the cluster where you will configure the service group.

For more information on installing and configuring Cluster Server, refer to the Cluster Server installation and configuration guides.

- Verify that the Cluster Server agent for Informatica PowerCenter Service Manager is installed on all nodes in the cluster.

See [“Installing the agent in a VCS environment”](#) on page 23.

Configuring PowerCenter Service Manager resources for Solaris zones support

To enable the agent for Informatica PowerCenter Service Manager to support Solaris zones, ensure that you perform the following configuration steps:

- Install PowerCenter Service Manager on dedicated Solaris zones.
- Preferably, follow the Veritas recommendation of installing zones on a shared disk for convenient configuration, failover, and maintenance.
- Make sure that the name of the Solaris zone is the same as the virtual host name that you use to install and configure the PowerCenter Service Manager.
- In a VCS environment, ensure that you have set the value of ContainerName attribute to the name of the Solaris zone.

By default, the agent function executes in the Global zone.

Instructing JRE to start running within a “headless” environment

For PowerCenter 8.1.1, the startup script `infaservice.sh` by default, does not start the underlying Tomcat server with the “headless” option. It is this process that the agent searches in order to flag the application as ONLINE.

If the “headless” option is not used then rendering of charts do not work on the PowerCenter Administration Console. This is because the Java process is not able

to render the charts, as it lacks the GUI/X-Window capability for doing this. This, however, has no bearing on the repository or integration service operation.

To instruct the JRE to start the Tomcat “headless” process, add the following lines to the environment file being registered with the EnvFile agent attribute:

```
INFA_JAVA_OPTS="-Xmx512m -Djava.awt.headless=true"  
  
export INFA_JAVA_OPTS
```

This example assumes an environment file for the Bourne-shell. Bounce the entire PC domain after making this change.

Troubleshooting the agent for Informatica PowerCenter Service Manager

This chapter includes the following topics:

- [Using the correct software and operating system versions](#)
- [Meeting prerequisites](#)
- [Configuring PowerCenter Service Manager resources](#)
- [Verifying virtualization](#)
- [Starting the PowerCenter Service Manager instance outside a cluster](#)
- [Reviewing error log files](#)

Using the correct software and operating system versions

Ensure that you use correct software and operating system versions.

For information on the software versions that the agent for Informatica PowerCenter Service Manager supports, see the Veritas Services and Operations Readiness Tools (SORT) site: <https://sort.veritas.com/agents>.

Meeting prerequisites

Before installing the agent for Informatica PowerCenter Service Manager, ensure that the following prerequisites are met.

For example, you must install the ACC library on VCS before installing the agent for Informatica PowerCenter Service Manager.

See [“Before you install the Cluster Server agent for Informatica PowerCenter Service Manager”](#) on page 19.

Configuring PowerCenter Service Manager resources

Before using PowerCenter Service Manager resources, ensure that you configure the resources properly. For a list of attributes used to configure all PowerCenter Service Manager resources, refer to the agent attributes.

Verifying virtualization

Verify that your application does not use anything that ties it down to a particular node of the cluster.

See [“Virtualizing PowerCenter Service Manager”](#) on page 17.

Starting the PowerCenter Service Manager instance outside a cluster

If you face problems while working with a resource, you must disable the resource within the cluster framework. A disabled resource is not under the control of the cluster framework, and so you can test the PowerCenter Service Manager instance independent of the cluster framework. Refer to the cluster documentation for information about disabling a resource.

You can then restart the PowerCenter Service Manager instance outside the cluster framework.

Note: Use the same parameters that the resource attributes define within the cluster framework while restarting the resource outside the cluster framework.

Execute the following commands to start, stop or monitor the Service Manager Server outside the cluster framework.

To start	<code>\$ InfaHome/server/tomcat/bin/infaservice.sh startup</code>
To stop	<code>\$ InfaHome/server/tomcat/bin/infaservice.sh shutdown</code>
To monitor	<p>Verify whether the PowerCenter Service Manager processes are running as InfaUser by executing the following command.</p> <pre>\$ telnet HostName Port</pre> <p>Note: The agent uses the connect (3c) method to check whether Administration Console of the PowerCenter Service Manager is listening to the port defined by the <i>Port</i> agent attribute on the host defined by the <i>HostName</i> agent attribute.</p>

Reviewing error log files

If you face problems while using PowerCenter Service Manager or the agent for Informatica PowerCenter Service Manager, use the log files described in this section to investigate the problems.

If you face problems while using PowerCenter Service Manager or the agent for Informatica PowerCenter Service Manager, refer to your product documentation to locate the log files, to investigate the problems.

The common reasons for issues are as follows:

Insufficient privileges	Files that need to be created, written to, would be created as InfaUser. Check if necessary privileges have been set.
Incorrect port, environment or parameter settings	<p>Verify that ports have been properly configured and declared. Typically, ports from 1 through 1024 are reserved for the superuser.</p> <p>Ensure that parameters to the agent are correctly defined.</p>
Expired licenses	<p>Check the application log files for any error messages related to expired licenses.</p> <p>Ensure that the license keys/files have been placed at the appropriate location, as needed by the application.</p>
Broken symlinks, missing files, and libraries	<p>Verify your installation.</p> <p>Make sure that nothing is broken, and all dependencies for the executables are met.</p>

Insufficient disk space or system parameters

Ensure that the file-system has sufficient space for creation of temporary files that the application might need.

Verify that the kernel has been tuned for sufficient IPC resources, file descriptors and meets the hardware requirement. Consult your product documentation for these details.

Consult your application expert if needed.

Reviewing cluster log files

In case of problems while using the agent for Informatica PowerCenter Service Manager, you can access the engine log file for more information about a particular resource. The engine log file is located at `/var/VRTSvcS/log/engine_A.log`.

Using trace level logging

The `ResLogLevel` attribute controls the level of logging that is written in a cluster log file for each PowerCenter Service Manager resource. You can set this attribute to `TRACE`, which enables very detailed and verbose logging.

If you set `ResLogLevel` to `TRACE`, a very high volume of messages are produced. Veritas recommends that you localize the `ResLogLevel` attribute for a particular resource.

Note: Starting with version 5.1.1.0 of the ACC library, the `TRACE` level logs for any ACCLib based agent are generated locally at the location `/var/VRTSvcS/log/Agent_A.log`.

The `LogDbg` attribute should be used to enable the debug logs for the ACCLib-based agents when the ACCLIB version is 6.2.0.0 or later and the VCS version is 6.2 or later.

To localize `ResLogLevel` attribute for a resource

- 1 Identify the resource for which you want to enable detailed logging.
- 2 Localize the `ResLogLevel` attribute for the identified resource:

```
# hares -local Resource_Name ResLogLevel
```

- 3 Set the `ResLogLevel` attribute to `TRACE` for the identified resource:

```
# hares -modify Resource_Name ResLogLevel TRACE -sys SysA
```

- 4 Test the identified resource. The function reproduces the problem that you are attempting to diagnose.

- 5 Set the ResLogLevel attribute back to INFO for the identified resource:

```
# hares -modify Resource_Name ResLogLevel INFO -sys SysA
```

- 6 Save the configuration changes.

```
# haconf -dump
```

- 7 Review the contents of the log file.

You can also contact Veritas support for more help.

To enable debug logs for all resources of type PowerCenterSvcMgr

- ◆ Enable the debug log.

```
# hatype -modify PowerCenterSvcMgr LogDbg DBG_5
```

To override the LogDbg attribute at resource level

- ◆ Override the LogDbg attribute at the resource level and enable the debug logs for the specific resource.

```
# hares -override PowerCenterSvcMgr LogDbg
# hares -modify PowerCenterSvcMgr LogDbg DBG_5
```

Sample Configurations

This appendix includes the following topics:

- [About sample configurations for the agents for Informatica PowerCenter Service Manager](#)
- [Sample agent type definition](#)
- [Sample agent type definition under Solaris zones](#)
- [Sample configuration](#)
- [Sample configuration under Solaris zones](#)
- [Sample service group configurations](#)
- [Sample service group configuration under Solaris zone](#)

About sample configurations for the agents for Informatica PowerCenter Service Manager

The sample configuration graphically depicts the resource types, resources, and resource dependencies within the service group. Review these dependencies carefully before configuring the agents for Informatica PowerCenter Service Manager. For more information about these resource types, refer to the *Cluster Server Bundled Agents Reference Guide*.

Sample agent type definition

The sample agent type definition for Informatica PowerCenter Service Manager are as follows:

For VCS 4.x

```

type PowerCenterSvcMgr (
    static int RestartLimit = 1000
    static str ArgList[] = { ResLogLevel, State, IState,
        InfaUser, EnvFile, HostName, Port, InfaHome,
        SecondLevelMonitor, MonitorProgram }
    str ResLogLevel = INFO
    str InfaUser
    str EnvFile
    str HostName
    int Port = 6001
    str InfaHome
    int SecondLevelMonitor = 0
    str MonitorProgram
)

```

For VCS 5.0

```

type PowerCenterSvcMgr (
    static int RestartLimit = 1000
    static str AgentFile = "/opt/VRTSvcs/bin/Script50Agent"
    static str AgentDirectory = "/opt/VRTSagents/ha/bin/
        PowerCenterSvcMgr"
    static str ArgList[] = { ResLogLevel, State, IState,
        InfaUser, EnvFile, HostName, Port, InfaHome,
        SecondLevelMonitor, MonitorProgram }
    str ResLogLevel = INFO
    str InfaUser
    str EnvFile
    str HostName
    int Port = 6001
    str InfaHome
    int SecondLevelMonitor = 0
    str MonitorProgram
)

```

Sample agent type definition under Solaris zones

```

type PowerCenterSvcMgr (
    static str ContainerType = Zone
    static str AgentDirectory = "/opt/VRTSagents/ha/bin/
        PowerCenterSvcMgr"
    static str AgentFile = "/opt/VRTSvcs/bin/Script50Agent"
    static int RestartLimit = 1000
)

```



```

static il8nstr ArgList[] = { ResLogLevel, State, IState,
InfaUser, EnvFile, HostName, Port, InfaHome,
SecondLevelMonitor, MonitorProgram }
str ResLogLevel = INFO
str InfaUser
str EnvFile
str HostName
int Port = 6001
str InfaHome
int SecondLevelMonitor
str MonitorProgram
str ContainerName
)

```

Sample configuration

The sample agent type definition for Informatica PowerCenter Service Manager is as follows:

```

include "types.cf"
include "CFSTypes.cf"
include "CVMTypes.cf"
include "PowerCenterSvcMgr.cf"

cluster PowerCenter (
  UserNames = { admin = eHlAHCHEIdIlgQIcHF }
  ClusterAddress = "10.182.4.208"
  Administrators = { admin }
  UseFence = SCSI3
  HacliUserLevel = COMMANDROOT
)

system nodeA(
)

system nodeB (
)

group ClusterService (
  SystemList = { nodeA= 0, nodeB = 1 }
  UserStrGlobal = "LocalCluster@https://10.182.4.208:8443;"
  AutoStartList = { nodeA, nodeB }
  OnlineRetryLimit = 3
)

```

```
OnlineRetryInterval = 120
)

IP webip (
    Device = eth0
    Address = "10.182.4.208"
    NetMask = "255.255.224.0"
)

NIC csgnic (
    Device = eth0
)

VRTSWebApp VCSweb (
    Critical = 0
    AppName = vcs
    InstallDir = "/opt/VRTSweb/VERITAS"
    TimeForOnline = 5
    RestartLimit = 3
)

VCSweb requires webip
webip requires csgnic

// resource dependency tree
//
// group ClusterService
// {
//   VRTSWebApp VCSweb
//   {
//     IP webip
//     {
//       NIC csgnic
//     }
//   }
// }

group Informatica_cfs (
    SystemList = { nodeA= 0, nodeB = 1 }
    AutoFailOver = 0
    Parallel = 1
```

```
AutoStartList = { nodeA, nodeB }
)

CFSMount infabin_mnt (
    MountPoint = "/u01/app/infa_bin"
    BlockDevice = "/dev/vx/dsk/infa_bindg/infa_binvol"
    MountOpt = largefiles
)

CFSMount infashared_mnt (
    MountPoint = "/u01/app/infa_shared"
    BlockDevice = "/dev/vx/dsk/infa_shareddg/infa_sharedvol"
    MountOpt = largefiles
)

CVMVolDg infabin_voldg (
    CVMDiskGroup = infa_bindg
    CVMActivation = sw
)

CVMVolDg infashared_voldg (
    CVMDiskGroup = infa_shareddg
    CVMActivation = sw
)

requires group cvm online local firm
infabin_mnt requires infabin_voldg
infashared_mnt requires infashared_voldg

// resource dependency tree
//
// group Informatica_cfs
// {
//   CFSMount infabin_mnt
//   {
//     CVMVolDg infabin_voldg
//   }
//   CFSMount infashared_mnt
//   {
//     CVMVolDg infashared_voldg
//   }
// }
```

```
group PowerCenterServiceManager (
    SystemList = { nodeB = 0, nodeA= 1 }
    AutoFailOver = 0
    Parallel = 1
    AutoStartList = { nodeB, nodeA}
)

PowerCenterSvcMgr Informatica (
    InfaUser = infaPC
    EnvFile @nodeB = "/u01/app/infa_bin/PowerCenter/nodeB/envfile"
    EnvFile @nodeA= "/u01/app/infa_bin/PowerCenter/nodeA/envfile"
    InfaHome @nodeB = "/u01/app/infa_bin/PowerCenter/nodeB"
    InfaHome @nodeA= "/u01/app/infa_bin/PowerCenter/nodeA"
)

requires group Informatica_cfs online local firm

// resource dependency tree
//
// group PowerCenterServiceManager
// {
//   PowerCenterSvcMgr Informatica
// }

group cvm (
    SystemList = { nodeA= 0, nodeB = 1 }
    AutoFailOver = 0
    Parallel = 1
    AutoStartList = { nodeA, nodeB }
)

CFSfsckd vxfsckd (
)

CVMCluster cvm_clus (
    CVMClustName = PowerCenter
    CVMNodeId = { nodeA= 0, nodeB = 1 }
    CVMTransport = gab
    CVMTimeout = 200
)
```

```

)

CVMVxconfigd cvm_vxconfigd (
    CVMVxconfigdArgs = { syslog }
)

cvm_clus requires cvm_vxconfigd
vxfscsd requires cvm_clus

// resource dependency tree
//
// group cvm
// {
//     CFSfscsd vxfscsd
//     {
//         CVMCluster cvm_clus
//         {
//             CVMVxconfigd cvm_vxconfigd
//         }
//     }
// }
// }

```

Sample configuration under Solaris zones

This section provides a sample configuration under Solaris zone support for the agent for Informatica PowerCenter Service Manager.

```

include "types.cf"
include "CFSTypes.cf"
include "CVMTTypes.cf"
include "PowerCenterSvcMgrTypes50.cf"

cluster tpm-cluster-kr (
    UserNames = { admin = dqrJqlQnrMrrPzrLqo,
        z_inf_zone_tpm-lab-33 = ImnFmhMjnInnLvnHmk,
        z_inf_zone_tpm-lab-34 = cmnFmhMjnInnLvnHmk }
    ClusterAddress = "127.0.0.1"
    Administrators = { admin }
)

```

```
system tpm-lab-33 (
)

system tpm-lab-34 (
)

group cfs_inf_cfsmount1 (
  SystemList = { tpm-lab-34 = 0, tpm-lab-33 = 1 }
  AutoFailOver = 0
  Parallel = 1
  AutoStartList = { tpm-lab-33, tpm-lab-34 }
)

CFSMount cfsmount1 (
  Critical = 0
  MountPoint = "/mnt1"
  BlockDevice = "/dev/vx/dsk/shareddg1/testvol"
  MountOpt @tpm-lab-34 = "cluster"
  MountOpt @tpm-lab-33 = "cluster"
  NodeList = { tpm-lab-33, tpm-lab-34 }
)

CVMVolDg cvmvoldg1 (
  Critical = 0
  CVMDiskGroup = shareddg1
  CVMActivation @tpm-lab-34 = sw
  CVMActivation @tpm-lab-33 = sw
)

requires group cvm online local firm
cfsmount1 requires cvmvoldg1

// resource dependency tree
//
// group cfs_inf_cfsmount1
// {
//   CFSMount cfsmount1
//     {
//       CVMVolDg cvmvoldg1
//     }
// }
```

```
group cvm (
  SystemList = { tpm-lab-34 = 0, tpm-lab-33 = 1 }
  AutoFailOver = 0
  Parallel = 1
  AutoStartList = { tpm-lab-33, tpm-lab-34 }
)

CFSfsckd vxfsckd (
  ActivationMode @tpm-lab-34 = { sharedddl = sw }
  ActivationMode @tpm-lab-33 = { sharedddl = sw }
)

CVMCluster cvm_clus (
  CVMClustName = tpmclust
  CVMNodeId = { tpm-lab-33 = 0, tpm-lab-34 = 1 }
  CVMTransport = gab
  CVMTimeout = 200
)

CVMVxconfigd cvm_vxconfigd (
  Critical = 0
  CVMVxconfigdArgs = { syslog }
)

vxfsckd requires cvm_clus
cvm_clus requires cvm_vxconfigd

// resource dependency tree
//
// group cvm
// {
//   CFSfsckd vxfsckd
//   {
//     CVMCluster cvm_clus
//     {
//       CVMVxconfigd cvm_vxconfigd
//     }
//   }
// }
```

```
group powercentersvcmgr_zone (
    SystemList = { tpm-lab-33 = 0, tpm-lab-34 = 1 }
    Parallel = 1
    AutoStartList = { tpm-lab-33, tpm-lab-34 }
)

NIC powercentersvcmgr_nic (
    Device = bge0
)

PowerCenterSvcMgr powercenterssvcmgr_res (
    InfaUser = infa
    EnvFile = "/home2/infa/.profile"
    HostName @tpm-lab-33 = inf1
    HostName @tpm-lab-34 = inf2
    InfaHome @tpm-lab-33 = "/u01/app/infa_bin/PowerCenter8.6.1/inf1"
    InfaHome @tpm-lab-34 = "/u01/app/infa_bin/PowerCenter8.6.1/inf2"
    SecondLevelMonitor = 1
    ContainerName @tpm-lab-33 = inf1
    ContainerName @tpm-lab-34 = inf2
)

Zone powercentersvcmgr_zone (
    ZoneName @tpm-lab-33 = inf1
    ZoneName @tpm-lab-34 = inf2
)

requires group cfs_inf_cfsmount1 online local firm
powercenterssvcmgr_res requires powercentersvcmgr_zone
powercentersvcmgr_zone requires powercentersvcmgr_nic

// resource dependency tree
//
// group powercentersvcmgr_zone
// {
//   PowerCenterSvcMgr powercenterssvcmgr_res
//   {
//     Zone powercentersvcmgr_zone
//     {
//       NIC powercentersvcmgr_nic
//     }
//   }
// }
```




```
// }
```

Sample service group configurations

This section includes the sample service group configurations in a VCS environment.

[Figure A-1](#) shows the service group dependency between CVM, CFS and PowerCenter service groups.

Figure A-1 Group dependency of service groups for CVM, CFS and PowerCenter Service Manager



[Figure A-2](#) shows a service group for Cluster File System.

Figure A-2 Sample service group for Cluster File System




Figure A-3 shows a service group for Cluster Volume Manager.

Figure A-3 Sample service group for Cluster Volume Manager





Figure A-4 shows the resource view of PowerCenter Service Manager on all systems.

Figure A-4 Resource view of PowerCenter Service Manager on all systems




Sample service group configuration under Solaris zone

This section includes the sample service group configurations under Solaris zone.

[Figure A-5](#) shows a service group for a PowerCenter Service Manager instance, if the virtual IP used by the application is identical to the zone name.

Figure A-5 Service group for a PowerCenter Service Manager instance, if the virtual IP used by the application is identical to the zone name.



[Figure A-6](#) shows the sample service group for Cluster Volume Manager

Figure A-6 Sample service group for Cluster Volume Manager




Figure A-7 shows the sample service group for Cluster File System

Figure A-7 Sample service group for Cluster File System





Figure A-8 shows the Group dependency of service groups for CVM, CFS and PowerCenter Service Manager under Solaris zones

Figure A-8 Group dependency of service groups for CVM, CFS and PowerCenter Service Manager under Solaris zones



Index

A

- about
 - configuring service groups 39
- about ACC library 20
- ACC library
 - installing 21
 - removing 28
- agent
 - features 11
 - importing agent types files 32
 - installing, VCS environment 23
 - optional attributes 36
 - overview 10
 - required attributes 34
 - uninstalling, VCS environment 27
 - upgrading 29
- agent attributes 34
 - EnvFile 35
 - HostName 36
 - InfHome 36
 - InfUser 35
 - MonitorProgram 36
 - port 35
 - ResLogLevel 35
 - SecondLevelMonitor 37
- agent configuration file
 - importing 32
- agent functions 12
 - clean 14
 - monitor 13
 - offline 13
 - online 12
- agent installation
 - general requirements 19
 - requirements for Solaris zones 20
 - steps to install 23

B

- before
 - configuring the service groups 40

C

- changing default restart behaviour 34
- clustering Service Manager Server
 - basic resources 16
- configuring monitor function 37

E

- executing custom monitor program 37

I

- Informatica PowerCenter Service Manager
 - configuring resources for Solaris zones 40

L

- logs
 - reviewing cluster log files 45
 - reviewing error log files 44
 - using trace level logging 45

P

- PowerCenter Service Manager
 - configuring resources 43
 - starting instance outside cluster 43
 - virtualization 17
 - Host names 18
 - Path names 18

S

- sample agent type definition 47
- Sample agent type definition under Solaris zones 48
- Sample configuration
 - under Solaris zones 53
- sample configuration 49
- Sample service group configuration
 - under Solaris zone 59
- sample service group configurations 57
- service group
 - sample configurations 57

- Service Manager Server
 - clustering
 - basic resources 16
- setting
 - PowerCenter Service Manager in a cluster 14
- Solaris zone support
 - configuring PowerCenter Service Managerresources 40
 - installation requirements 20
- Solaris zones support
 - Sample configuration 53
- starting the PowerCenter Service Manager instance
 - outside a cluster 43

T

- troubleshooting
 - meeting prerequisites 43
 - reviewing error log files 44
 - reviewing cluster log files 45
 - using trace level logging 45
 - using correct software 42
 - verifying virtualization 43

U

- uninstalling agent, VCS environment 27
- upgrading agent 29